
WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- PIPER PET.
Farm- Braun "B" No. 2

SEC. 2 T. 14 R. 17W
NE NE NW

Total Depth. 3462'
Comm. 4/14/56 Comp. 5/7/56
Shot or Treated.
Contractor. Tom Allan
Issued. 7-28-56

County Ellis
KANSAS



Elevation. 1949 RB

Production 75 BOPD & NW

CASING:
8 5/8" @ 900' 320 Sx.
5 1/2" @ 3462' 150 Sx.

Figures Indicate Bottom of Formations.

soil	60
limy shale	250
sandstone & shale	700
red beds	1120
Anydrite	1150
red shale	1350
sahel & salt	1800
Anhydrite, lime & shale	2500
shale	2916
lime & shale breaks	3170
black shale	3174
lime & shale breaks	3205
red & gray shale	3216
lime	3242
soft lime, S.S.O. Sat.	3246
lime	3260
soft lime, S.S.O. Sat.	3266
lime	3286
soft Oolitic lime, S.O. stained	3290
lime	3297
soft lime, S.S.O. sat.	3302
lime	3345
Cherty lime, S.O. stain	3350
lime	3430
red & gray shale & lime streaks	3460
CHANGED TO CABLE TOOLS @	3462
Chrystaline Dolomite	3469
Total Depth	

All Depths from Rotary Bushings
Ran Lane Well Log

TOPS:

Anhydrite	1120
Heebner	3170
Lansing	3216
Arbuckle	3460

D.S.T. #1 3218-3250/60 Min.
900' Gas, 240' O & G CM
280' Muddy - BHP 480#/

D.S.T. #2 3254-3276/60 Min.
285' Salt Water
BHP 440#/

D.S.T. #3 3284-3353/60 Min.
510' Salt Water
BHP 1000#/

Perforated again 15 holes 3243-47
Test 93 gal water in 8 hours
Acid 300 gal.
Test 24 bbl. water/8 hours
Cement squeeze, 105 Sx.

Reopened Arbuckle
Test 3 bbl. Oil/hr. no water