

TAYLOR & RANSOM
Emery No. 1.

SEC. 23 T. 14 R. ~~1~~
NEc NE


18W

54025

Total Depth. 3576
Comm. 9-12-36 Comp. 12-20-36
Shot or Treated. 1000 gal.
Contractor. Brunson Drlg Co.
Issued. 1-23-37

County Ellis.

CASING.
15 1/2" 50' 6" 3289'
12 1/2" 890' 284' of 53/16 liner at 3566'
10" 1165'
8" 2645'



Elevation.

Production. Dry.

Figures Indicate Bottom of Formations.

surface	20	lime	1890	shale	2760
clay	35	shale	1900	lime	2780
gravel water	40	lime	1910	lime	2790
shale	50	lime	1945	shale	2810
shale blue	65	shale	1950	lime	2815
shale blue	230	lime	1985	shale	2825
shale white	250	shale	1995	lime	2870
shale	285	red rock	2000	lime broken	2885
sand	293	shale	2010	lime broken	2900
shale	320	lime	2030	shale	2940
red rock	350	lime	2055	lime	2935
shale blue	355	shale	2080	1 1/2 BW 2990-2995	
red rock	375	lime	2120	lime broken	2945
10 BW 285-293		lime	2165	red rock	2955
red rock	395	shale	2175	shale	2960
sdv shale blue	430	lime	2190	lime	2995
4 BWPH 395 HFW 410		lime	2200	shale	2999
shale blue	475	shale and shells	2210	lime	3015
shale dark	490	red rock	2220	slight sh oil	3290-95
shale blue	545	lime	2230	lime	3317
sand and lime	555	shale	2235	shale	3320
shale wtr 600	580	shale	2245	lime	3340
shale and sand	630	lime	2270	oil showing	3335-40
sand and shale	790	shale	2285	and 1 1/2 B.W.	
more wtr 660		lime	2305	lime	3380
red rock	820	lime	2310	shale	3385
red sand	830	shale	2315	lime	3403
shale red	880	lime	2325	shale	3406
red rock	925	shale	2330	lime	3445
shale red	970	red rock	2340	shale	3450
shale red	1162	shale	2350	lime	3455
Anhydrite	1165	lime	2395	lime	3480
lime	1196	red rock	2400	lime broken	3497
red rock-	1200	2 BW 2375-80		red rock	3505
lime	1206	red rock	2410	lime	3509
red rock	1342	lime	2440	conglomerate	3515
shale blue	1355	shale	2450	conglomerate	3553
red rock	1360	lime	2510	Top Sil lime.	3553
shale blue	1375	shale	2520	lime soft sh oil	3566
red rock	1468	2 BW 2495-2500		lime hard	3572
shale blue	1478	shale	2525	lime soft Oil	3576
red rock	1490	lime	2540	Total Depth.	
shale blue	1500	shale	2545		
shale	1545	lime and shale	2560	Plugged back to 3566 with	
salt	1600	shale and shells	2580	lead wool and cement.	
salt	1780	shale	2645	Perforated liner, acidized	
shale and lime	1810	lime hard	2665	1000 gal acid. Prod. 20-40 B.	
lime	1815	shale	2675	daily, with some wtr.	
red rock	1825	lime	2705	28° gravity Abd.	
lime	1850	shale	2730	Depths are corrected to	
				Lane Well Meas.	

3509
1959
1550

3566
288
3282