


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- WYCOFF-WILLIAMS DRILLING COMPANY
 Farm- R. L. Lundgren No. 1

SEC. 31 T. 14 R. 29W
 NE NE SW

Total Depth. 4332
 Comm. 7-28-52 Comp. 8-13-52
 Shot or Treated. 2500 gal. acid
 Contractor. Company Tools
 Issued. 10-18-52

County Gove KANSAS



Elevation. 2613

Production. 236 BO

Figures Indicate Bottom of Formations.

surface soil & clay	100
shale	128
shale & sand	310
lime, milky	390
shale	458
shale sandy	950
sand	1150
shale & shells	1240
shale	1385
sand sharp	1395
shale & shells	1520
shale	1660
sand	1780
shale	1930
red bed & shale	2040
anhydrite	2070
red bed & shale	2305
shale & shells	2505
shale & lime	2775
shale	3085
shale & shells	3150
lime & shale	3310
shale	3405
shale & lime	3505
lime & shale	3575
lime, cherty	3645
lime	3695
lime	3763
lime & shale	3770
lime	3860
lime	3930
shale & lime	3980
lime	4005
shale & lime	4115
lime, cherty	4154
lime	4277
lime & dolomite	4331
lime & dolo.	4332
Total Depth	

Tops:
 Heebner Shale 3639
 Lansing-K. C. 3674
 Marmaton Lime 3990
 Miss. Lime 4263

Slight stain throughout 3674'
 Slight show at 4210'
 good show of oil 4263'

Rotary Total Depth 4332
 Cable Tool T. D. 4300