1-15-26W


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- D. R. LAUCK OIL CO., INC.
Farm- Stutz No. 1

SEC. 1 T. 15 R. 26W
C SE SE

Total Depth. 4287'
Comm. 11-13-64 Comp. 11-26-64
Shot or Treated.
Contractor. Co. Tools
Issued. 1-30-65

County Gove
KANSAS



Elevation. 2271 D F

Production. Dry

CASING:
8 5/8" 211' cem. w/160 sx.
& 3 sx. Calcium Chloride

Figures Indicate Bottom of Formations.

| | |
|---|---|
| sand | 19 |
| rock | 30 |
| shale | 830 |
| sand | 909 |
| shale | 990 |
| redbed, shale, shells | 1165 |
| shale w/sand streaks | 1535 |
| shale, redbed & shells | 1750 |
| Anhydrite & shale | 1790 |
| shale & shells | 2281 |
| shale w/lime streaks | 2380 |
| shale & lime | 2697 |
| lime & shale | 2784 |
| shale & lime | 2935 |
| lime & shale | 3045 |
| shale & lime | 3490 |
| lime & shale | 3590 |
| lime | 3663 |
| lime & shale | 3725 |
| lime | 3825 |
| lime & shale | 3862 |
| lime | 3990 |
| lime & shale | 4212 |
| sand & Chert | 4216 |
| Cherty lime & shale | 4245 |
| lime | 4287 |

Rotary Total Depth

DST #1. 4192-4216, Op. 1 hr. w/weak blow 13 Min. Rec. 3' drilling muc. ISIP 61#/30 Min. FSIP 61#/30 min. IFP 36#, FFP 36#

| TOPS | Sample | Welex |
|---|---|---|
| Anhydrite | 1750 | |
| Heebner | 3561 | 3562 |
| Toronto | 3580 | 3582 |
| Lansing | 3600 | 3603 |
| Base Kansas City | 3893 | 3894 |
| Pawnee | 3997 | 4004 |
| Fort Scott | 4037 | 4040 |
| Cherokee Shale | 4095 | 4095 |
| Sand | 4198 | 4195 |
| Mississippian | 4232 | 4216 |