


15-15-11W
SEC. 15 T. 15 R. 11W.
NEo SW

R.E.DAY
Nuss No. 1

Total Depth. 3301
Comm. 8-20-41 Comp. 3-25-42
Shot or Treated.
Contractor.
Issued. 5-2-42

County Russell



CASING.

13"	350'
10"	590'
8 1/2"	2287'
7"	2905'
5 1/2"	3279

Elevation.

Production. DRY

Figures Indicate Bottom of Formations.

soil	20	lime	1893	conglomerate	3176
sdv shale	35	broken lime	1900	lime	3190
shale	60	lime	1915	conglomerate	3253
sdv shale	65	shale	1920	shale green	3257
shale	80	lime	1955	lime	3301
red rock	120	shale brown	1960		
		lime	1985	Total Depth.	
lime	125	shale blk	1990		
shale	160	lime	2000		
red rock	210	lime and shale	2050		
shale	245	shale & shells	2110		
sand water	260	shale	2120		
shale	315	lime	2130		
sand	320	shale brown	2135		
shale	350				
lime	355	lime	2160		
		shale Brown	2175		
		lime	2180		
shale blue	400	shale	2190		
red shale	405	shale shells	2250		
red rock	485	lime	2250		
red shale	550				
red rock	585	shale shells	2295		
red shale	590	shale	2315		
anhydrite	625	lime	2320		
red rock	735	shale shells	2365		
		shale	2380		
shale blue	840	shale	2387		
lime	845	lime broken	2405		
shale	860	shale	2420		
red rock	880	lime	2435		
lime	890	lime broken	2460		
red rock	910	lime	2475		
shale	970	lime&shale	2500		
lime shells	985	lime	2540		
shale	1015				
salt	1235	sdv lime	2550		
shale	1240	lime	2755		
lime	1255	shale	2758		
shale	1260	lime	2815		
lime	1360	red rock	2818		
broken lime	1380	shale	2860		
red rock	1385	lime	2900		
lime	1435	lime	2950		
shale	1445	shale	2957		
lime	1580	lime	3010		
shale lime	1620	sdv lime	3022		
sdv lime	1625	lime	3060		
lime	1650	shale	3063		
red rock	1660	lime	3090		
lime	1735	shale	3096		
red rock	1747	lime	3125		
lime	1760	shale	3130		
red rock	1770	lime	3155		
broken lime	1790				

WATER RECORD.

12 BW 60 to 160
HFW 245 to 260
HFW 270 to 300
HFW 445 to 600
1/4 BW 1620 to 1640
1/2 BW 1960 to 1975
1/2 BW 2050 to 2150
1/2 BW 2190 to 2260
1 BW 2540 to 2550
1 BW 2985 to 2990
HFW 3140 to 3145
HFW 3277 to 3301