


33-15-11W

TEXAS COMPANY
 Borrell No. 2.

SEC. 33 T. 15 R. 11 W
 CSE NW

Total Depth. 3280½'
 Comm. 5-31-43 Comp. 6-19-43
 Shot or Treated. 500 Gals. Acid 6-22-43
 Contractor. Pryor & Lockhart, Inc.
 Issued. 7-24-43

County. Russell



CASING:
 10" 383' Cem. LI
 5½" 3270' Cem. LI

Elevation.

Production. Pot. 142 B.

Figures Indicate Bottom of Formations.

clay, sand & shells	0-70
sand	85
shale & sand	130
shale	160
shale & shells	220
lime	223
shale & shells	260
sand	273
shale & lime	305
sand	345
shale & shells	394
shale blue	450
red rock	650
anhydrite lime	688
red rock	800
shale & shells	1095
salt	1200
shale & salt	1320
lime brkn	1505
lime & shale	1605
lime	1630
lime brkn & shale	1745
lime	1765
lime brkn	1837
lime & shale	1887
lime sdy	1895
lime & shale	2115
shale & shells	2205
lime & shale	2310
lime	2330
shale	2380
lime	2395
lime & shale	2465
shale & shells	2555
shale	2565
lime	2780
lime sft	2800
lime & shale	2873
shale	2880
lime brkn	2905
lime	2990
lime & shale	3135

Time	3249
lime cherty	3274
lime Arbuckle	3280½
Total Depth.	

Tops:	
Anhydrite	650
K. C. Lansing	2940
Arbuckle	3274