

15-15-13W

SINCLAIR PRAIRIE OIL CO.
Charles Sellens No. 2

SEC. 15 T. 15 R. 13W.
NE SW SW
990' N fr SL 990' E fr WL SW $\frac{1}{4}$

Total Depth. 3333
Comm. 3-18-40 Comp. 4-6-40
Shot or Treated. 2000 gal acid.
Contractor. Harbar Drlg. Co.
Issued. 7-6-40

County Russell.



CASING.

13" 115'
85/8" 3330'
2 $\frac{1}{2}$ " tubing 2334'

Elevation.

Production. Pot. 1391 B.
No wtr

Figures Indicate Bottom of Formations.

DRILLERS LOG.

cellar	3'7
Sub soil and lime	38
sand and shells	115
lime and shells	200
sand	240
shells and shale	320
lime shells	395
shale and shells	550
red rock and shale	645
red bed and shale	840
anhydrite	860
lime	870
shale and red rock	903
shale and shells	1015
shale and lime	1090
shale and shells	1240
shale and salt	1260
salt shells shale	1480
shale	1540
lime and shale	1575
anhydrite & shale	1675
lime and shale	1705
anhydrite and shale	1710
shale and lime	1730
anhydrite lime shale	1734
shale and lime	1800
lime	1860
shale and lime	1890
lime	1920
shale and lime	2120
brown shale	2135
broken lime	2145
lime	2175
shale and lime	2490
broken shale	2540
lime and shale	2765
lime	3020
shale and lime	3040
shale	3060
shale and lime	3094
lime soft	3099
lime	3155
lime soft	3174
lime	3198
broken lime	3208
lime	3314
lime and shale	3329
Arbuckle lime	3333
Total Depth.	

Top Arbuckle lime 3329