

W.I.SOUTHERN, INC.
Weimeister No. 1.

Sec. 3 T. 15 R. 13W.
NEo NW

Total Depth. 3300
Comm. 8-20-38 Comp. 9-27-38
Shot or Treated.
Contractor. Ruso Drlg.Co.
Issued. 11-5-38

County Russell.



CASING.

103/4" 260'
7" 2976'
5 1/2" 3053'

Elevation. 1780

Production. DRY.

Figures Indicate Bottom of Formations.

shale and shells	200
sand	220
shale and shells	500
red bed	565
red bed and shale	720
anhydrite	768
shale	1100
shale and shell	1140
salt	1315
shale and shell	1445
shale	1495
shale and shell	1560
shale and lime	1620
lime and shale	1920
lime	2030
lime and shale	2100
shale	2195
lime and shale	2610
lime	2918
shale white	2949
shale green	2955 1/2
denso grey limo	2958
brkon limo & shalo	2964
shalo rod and grey	2972
lime denso grey	2976
lime hard	2978
lime soft	2990
limo	3046
shalo and broken limo	3050
limo	3082
lime hard	3091 1/2
shalo lime sholls	3109
limo	3114
shalo lime sholls	3128
shalo and lime	3141
shalo lime sholls	3158
shalo blau	3176
rod rock	3181
lime	3192
limo and shalo	3203
limo	3210
shalo lime sholls	3253
conglomerate	3295 1/2 BW 3076-3080
water sand	3300

CORE No. 1.

from 2918-2934 10' Roc. thin
streaks of fino sand.

CORE No. 2

2940 to 2958' 2940 to 49 shalo with
streaks of sand.

2949 to 55 1/2 grey shalo
2955 1/2 to 58' denso grey limo

CORE No. 3

2958-2976

From 2958-64' broken limo and shalo

2964-72' rod and grey shalo.

with small streaks of limo

2972 to 76 denso grey limo

Top K.C. Lansing 2972

3298

326

2972
1780
-1192

3298
1780
-1518

Total Depth. Top Siliceous 3298