

Cable

DESCRIPTION

W.C.

Top	Bottom	Formation and Remarks
160	NL	35 L
85	R	55 I
220	I	70 L
50	R	75 I
55	-	90 L
60	L, -	1915 I
320	I	30 L
35	-	35 I
50	R	95 L
60	I	2010 R
75	R	30 L
85	L	70 I, X
90	R	2100 L
95	L	2245 I, X
645	R	75 I
98	R	95 R
710	L	2305 I
25	A	10 L
40	L	55 I
875	R	70 L
900	I	80 R
60	I	90 VL
1005	R	2422 I
1100	I	1BW 1750
1410	S	40 L
65	I, X	60 I
80	L	2525 I, X
1485	I	30 L
1510	L	60 I
15	I	75 L
30	I, X	90 I
40	L	2620 L
55	VL	30 I
1615	L	2765 L
20	I	70 I
45	R	90 L
50	L	2878 I
85	VL	95 L
TA 698		2900 R
1750	L	15 I
85	-I	29 L
1825	L	TLs 2929
30	I	T Dodge 2878

1745
TA 698
+1047
in

2929
1745
-1184
Ls.

in

State	Company
County	Farm
T. 15	R. 13W
	5
	0
Altitude	1745
Production	

CASING RECORD	
10"	710
8 1/4"	2422
20"	5 3/8" 2929
15 1/2"	230
12 1/2"	
Shot	Quarts
	Between

Top	Bottom	Formation and Remarks
330	2883	
4	13W	2705-15
45	L	
48	I	
70	L	
1	18W	(salt) per @ 2970
TD		2976 - 400' w inside
		P.B. 2950
		PB 2900
		perf 60 shots, 2870-
		86 - 5 barrels
		oil & some water
		50 for week
		hauled 10 barrel
		of water & 10 oil.
		1600 acid
		Pump 201 30-8 hrs
		PB-TD 2895
		grav 39°
		Pat 603
		no water