

WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
503 East Murdock, Wichita, Kansas

Company- SHIELDS OIL PRODUCERS
Form- Valin No. 1

SEC. 35 T. 15 R. 4W
CE/2 E/2 SW

Total Depth. 3424
Comm. 3-7-52 Comp. 3-20-52
Shot or Treated.
Contractor. Shields Drilling Co., Inc.
Issued. 8-9-52

County Saline
KANSAS



CASING:
8 5/8" 378' cem w/300 sx
5 1/2" 3423 1/2' cem w/ 50 sx

Elevation. 1315 RB

Production. SWB 5.4 BOPH/14 hrs,
no water

Figures indicate Bottom of Formations.

surface, sand	68
shale, shells	375
anhydrite	434
anhydrite broken	460
lime, shale	715
shale, shells	735
shale, red bed	805
lime, shale	1070
lime, shale, salt	1275
salt, shale	1310
lime, shale	1470
shale	1645
shale, lime	1975
lime	2075
shale	2200
lime, shale	2330
lime	2455
shale, lime	2838
shale	2890
shale broken	2930
lime, shale	3090
lime	3147
shale, brkn lime	3165
shale, lime	3268
shale	3424
Total Depth	

Tops:	
Miss.	2899
Hunton	3351
Maquoketa	3363
Maq. Dolomite	3423

Treatment: none.