

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY

508 E. Murdock,

Wichita, Kansas


6-16-10W

Company - SHIELDS & ANSCHUTZ DRG.,
Farm - Barclay No. 2

SEC. 6 T. 16 R. 10W
SW NW SW

Total Depth. 3363
Comm. 4-26-50 Comp. 5-14-50
Shot or Treated.
Contractor. Honaker Drlg. Co., Inc.
Issued. 6-10-50

County. Ellsworth
KANSAS



Elevation. 1867 ft. Ind.

Production. Swab 2 1/2 BPH.

CASING:

8 5/8" 338' cem. w/100 sx.
5 1/2" 3360' cem. w/ 75 sx.

Figures Indicate Bottom of Formations.

top soil & post rock	40
shale & iron	230
shale & shells	305
sand	325
shale & shells	335
sand & shale	375
shale & shells	510
red bed, shells	680
anhyd.	715
shale & shells	1179
salt & shale	1299
shale & lime	1360
lime	1600
lime & shale	1690
lime	2123
lime & shale	2650
lime	2670
lime & shale	2750
lime	2905
lime & shale	3010
lime	3363

Tops:
Topeka 2659
Hebner 2912
Toronto 2929
Lansing-K.C. 3028
Arbuckle 3357

T.D. 3360 D.F. Prod. 5 gals. oil per hr.
16 jet shows from 3357 1/2 to 3360
Treatment- 250 gals. acid.
Swabbed 2 1/2 bbls. oil per hr. for 8 hrs.-
no wtr.