


35-16-10W
Plotted Texas Co.

LAUCK & MONCRIEF ET AL
Meyer No. 2.

SEC. 35 T. 16 R. 10W
CNL NW
1320' fr WL 412' fr NL NW $\frac{1}{4}$

Total Depth. 3288'
Comm. 8-20-40 Comp. 9-6-40
Shot or Treated.
Contractor.
Issued. 9-21-40

County. Ellsworth



CASING:
10" 145' Cem.
7" 3279' Cem.

Elevation.

Production. Pot. 3000 B. Max.
Deptho.

Figures Indicate Bottom of Formations.

clay & shells	162
shale	480
red rock	545
shale	570
anhydrite	602
shale	810
shale & shells	1075
shale & salt	1275
shale	1290
anhydrite & lime	1305
shale & lime	1400
shale & shells	1445
lime	1465
lime brkn	1485
shale & lime	1605
lime sdy	1620
lime	1635
lime sdy	1664
shale & shells	1725
lime	1735
shale & lime	1770
lime brkn	1945
shale & lime	2105
shale & shells	2305
shale	2365
shale & lime	2470
shale	2525
lime brkn	2594
lime	2610
lime brkn	2630
shale & lime	2680
lime	2870
shale & shells	2900
shale	2940
lime	2990
lime porous	2997
lime	3010
shale & lime	3030
lime	3058
lime porous	3070
lime	3255
shale	3264
shale & lime	3265
chert & sdy shale	3267
shale green	3274 $\frac{1}{2}$

Potential - Depthograph 9-7-40 3000 B.
Max.

Tops: Lansing	2954 DF
Conglomerate	3266 DF Corr.
Simpson	3268 DF Corr.
Arbuckle	3279 DF Corr.

sand, smell oil	3277
shale green	3278
lime	3280

3278-3277 Derrick Floor

3280-3279 Derrick Floor

Standardized:

3277 rotary - 3279 Cable tools

3279 rotary T.D. - 3281 Cable tools

drilled plug & cleaned

out, sh free oil 3281

lime (saturation) 3286

lime (good pay) 3287 $\frac{1}{2}$

lime hrd 3288

3200' oil in hole

Total Depth.