

36-16-10W^{7m}


WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
412 Union National Bank Bldg, Wichita, Kansas.

LAUCK & MONCRIEF ET AL.
Ehler No. 6

SEC. 36 T. 16 R. 10W
CSL NW
467' fr SL 1320' fr WL NW $\frac{1}{4}$

Total Depth. 3288
Comm. 10-24-40 Comp. 11-9-40
Shot or Treated.
Contractor.
Issued. 1-11-41

County Ellsworth



CASING.

10" 148' cemented
7" 3279' cemented

Elevation

Production. Pot. 5528 B.
Depthograph.

Figures Indicate Bottom of Formations.

shale and shells	160		
shale shells and red rock	580	good fill up of oil	
shale and shells	602	lime	3285 $\frac{1}{2}$ Increase oil
anhydrite	625	lime	3287 Increase oil
shale and shells	1085	lime	3288 Increase oil
salt and shale	1165	Total Depth.	
salt	1300		
shale and lime	1460		
broken lime	1550		
lime	1595		
broken lime	1650		
sdv lime	1675		
lime	1825		
shale and lime	1900		
shale and shells	2310		
shale and lime	2370		
shale	2460		
shale and shells and			
sdv lime	2500		
broken lime	2675		
lime	2825		
broken lime	2885		
shale	2950		
broken lime	2975		
lime	2999		
lime porous	3005		
lime	3066		
lime porous	3081		
lime	3150		
lime porous	3161		
lime	3235		
shale and lime	3276		
lime	3281		
Standardized			
3276 rotary	3279 cable tools.		
3281 rotary	3284 cable tools.		
cement	3267-3279		
cleaned out rotary hole	3284		