


35-16-10W

LAUCK & MONCRIEF ET AL
 Meyer No. 1.

SEC. 35 T.16 R.10W
 NW¹/₄ NW
 440' fr WL 412' fr NL NW¹/₄

Total Depth. 3270'
 Comm. 5-21-40 Comp. 6-10-40
 Shot or Treated.
 Contractor.
 Issued. 8-3-40

County. Ellsworth



CASING:
 10" 146'
 7" 3262'

Elevation.

Production. Pot. 8446 B. Depth

Figures Indicate Bottom of Formations.

clay & shells	65
sand	90
shale	120
sand	135
shale & shells	161
red rock	180
shale & shells	360
sand	445
shale & shells	570
anhydrite	590
shale & shells	665
shale & lime brkn	830
shale & shells	1030
salt	1235
shale & salt	1270
shale & lime	1330
shale & shells	1455
lime brkn	1540
shale & lime	1600
lime sdy	1618
lime	1620
lime brkn	1665
lime	1810
shale & shells	1850
lime	1965
shale & lime	2010
lime brkn	2090
shale	2135
shale & lime	2255
shale & shells	2355
shale & lime	2415
shale & shells	2530
shale	2583
lime	2840
shale & lime	2872
rod rock	2875
shale	2945
lime	2980
lime brkn	3010
lime	3052
lime porous	3066
lime	3090
shale & lime	3105
lime	3220
lime brkn	3263

lime Arbuckle, sh oil	3265
Standardized: drilled plug	
2300' oil 1 1/4 hrs	
1000 Gals. Acid	
lime sft	3269
lime hrd	3270
3000' oil	
swabbed 50 B. 1 H. 900' off btm	
acidized 1000 Gals.	
Total Depth.	3270

Tops: Lansing 2947
 Arbuckle 3262 derrick floor