


29-16-11W

BLACK & MARSHALL
J.L.Wendlandt No. 1.

SEC. 29 T. 16 R. 11 W
CNE SE

Total Depth. 3348 $\frac{1}{2}$ '
Comm. 5-1-43 Comp. 5-20-43
Shot or Treated.
Contractor. Geo.H.Hannum, Inc.
Issued. 11-20-43

County. Barton



CASING:
10 $\frac{3}{4}$ " 276' Cem.
5 $\frac{1}{2}$ " 3333' Cem.(ground measure)

Elevation.

Production. Pot.136 B.

Figures Indicate Bottom of Formations.

shale & shells	257
sand	265
shale & shells	465
sand hd & sharp	525
Dakota shale	760
anhydrite	795
shale & shells	1275
salt	1425
shale & shells	1640
lime	1695
shale & shells	1800
lime	1855
lime & shale brks	1900
lime hd	1965
lime & shale brks	1995
shale	2010
shale & shells	2360
sand	2380
shale	2430
shale & shells	2530
lime brkn	2560
shale	2580
shale & shells	2680
lime	3339
sand	3341
lime	3348 $\frac{1}{2}$
Total Depth.	

Tops: K. C. Lime(DFM)3064
cored 3156-71
(full recovery)
cemented 5 $\frac{1}{2}$ " csg 2'
off btm, or 3333'
ground measure-60
sx cement
Arbuckle 3342