WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas

SHELL OIL CO.,INC.
F.F.Oeser No. 3.

SEC.17 T.16 R.11W
SW NW NW
991'fNL 330'fWL NW¼

Total Depth. 3306' PB3303'
Comm. 7-14-41 Comp. 8-2-41
Shot or Treated. 8-1-41 530 Gals. Acid 3294-3303
Contractor.
Issued. 9-20-41

County. Barton



Rotary 0-3295
Cable 3295-3306

CASING:
8 5/8" 331' Cem.
4 1/2" 3294' Cem.

Elevation.

Production. Deptho. Drawdown 1826 B. fluid 29%Wtr; Allowed Pot. 1296 B., 530BW

Figures Indicate Bottom of Formations.

shale & lime	30
sand & gravel	120
shale & lime	266
shale	310
shale & red rock	335
shale, sand, lime strks	480
shale red	700
anhydrite	730
shale	790
shale & lime	970
shale & lime strks	1150
salt & shale	1340
shale & lime strks	1385
shale & lime	1627
shale, lime, chert	1775
shale & lime	1850
lime	2113
lime & shale	2584
lime	3145
3145 equals 3144 SL Corr.	
lime	3291
conglomerate, shale red & green	3293
dolomite	3306
Total Depth.	

Plugged back 3303

Top Arbuckle dolomite 3293

400' oil 2 hrs 3297
2560' oil 8¼ hrs 3304
swb 64 BO, 6 BW 4 hrs 3306

Indicated capacity by Deptho.
draw-down test 1826 Bbls
fluid 29% wtr; allowed Pot.
1296 BO, 530 BW