WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas

SINCLAIR PRAIRIE OIL CO.
Edward Oeser No. 4.

SEC.17 T.16 R.11W
CNL NW SE
660'f W 330'f NL SE¼

Total Depth. 3292' PB 3287'
Comm. 5-26-41 Comp. 6-6-41
Shot or Treated.
Contractor. Harbar Drlg.Co.
Issued. 7-26-41

County. Barton



CASING:
10¾" 141' Cem.
5½" 3289' Cem.

Elevation.

Production. Pot.66 BO,
30% Wtr

Figures Indicate Bottom of Formations.

shale & shells	465
sand hrd	518
red bed shells	635
lime shells-hd	760
lime & shale	940
shale & shells	1135
shale & salt	1180
shale & shells	1735
lime & shale	1885
lime sdy	1890
lime	1920
shale	2075
lime & shale	2180
shale & shells	2455
lime brkn	2500
shale	2550
shale & lime	2665
lime	3054
lime sft	3101
lime	3285
shale & lime	3289?
lime	3292
Total Depth.	

Cement plug drld out
to only 3287

Perforated 5½" in K.C. lime
6 shots 3270-75 dry
30 shots 3262-69 fillup 70'
oil in 1 hr
12 shots 3263-67 fillup 80'
oil in 1 hr
Acidized 2000 Gals.

Potential 66 BO, 30% wtr, pmpd
w/ Contrs front after per-
forating & acidizing in K.C.

Top Conglomerate 3289