

BLACK-MARSHALL
Hitchman No. 1.

SEC.32 T.16 R.11 W
CSW SE

Total Depth. 3326'
Comm. 9-18-42 Comp. 11-10-42
Shot or Treated.
Contractor. Benson Drlg.Co.
Issued. 12-19-42

County. Barton



CASING:

13" 420' 7" 2950'
10" 760' 5 1/2" 3217'
8" 2118'

Elevation.

Production. Pot. 2479 B.

Figures Indicate Bottom of Formations.

cellar	8	lime	2240
lime	30	shale	2245
shale	160	lime	2265
shale red	180	shale	2285
shale	265	lime	2310
sand(HFW 265-90)	290	shale	2320
shale	340	lime	2330
sand	350	shale	2382
shale	400	lime	2385
sand	410	shale	2400
shale	430	lime	2430
sand(HFW 430-45 (iron 445-50)	450	shale	2470
shale	475	lime(1/2blr2420-60)	2492
lime	480	shale	2500
red rock	725	lime	2505
shale blue	733	shale	2510
lime-anhydrite	760	lime	2535
red rock	960	shale	2545
shale blue	1030	lime	2560
shale red	1065	shale	2590
shale	1175	lime	2595
salt	1412	shale	2610
shale blue	1420	lime	2615
lime	1430	shale	2620
shale red	1433	lime	2635
lime	1470	shale	2645
shale	1480	lime	2790
lime	1540	shale	2800
shale blue	1545	lime	2925
lime	1585	shale	2930
shale & shells	1650	lime	2935
shale red	1665	shale	2945
lime(1 1/2blr 1780-90)	1815	lime	2955
shale	1830	red rock	2957
lime	1835	shale	3025
shale	1845	lime	3030
lime	1875	shale	3038
shale	1890	1 million ft gas@3050	
lime	1895	lime	3255
red rock	1905	shale	3258
lime	1935	lime(sh oil 3258-62)	3288
shale	1945	shale	3292
red rock	1950	lime	3310
shale	1955	shale	3313
lime	2025	lime(oil 3317-20)	3326
shale red	2035	Total Depth.	
lime	2100		
shale	2115		
lime	2130		
shale	2145		
lime	2155		
shale	2160		
lime	2175		
shale	2180		
lime	2190		
shale	2195		
lime	2200		
shale	2220		