

5-16-11W

KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
KANSAS GEOLOGICAL SOCIETY BUILDING
508 EAST MURDOCK - WICHITA, KANSAS

COMPANY DUKE DRILLING

SEC. 5 T. 16 R. 11W

FARM Foster

NO. 1

LOC. NW NE NE

TOTAL DEPTH 3285'

COUNTY Barton


COMM. 2-14-67

COMP. 2-20-67

BHDT OR TREATED

CONTRACTOR Duke Drlg.

ISSUED 6-3-67



CASING

20	10		
15	8 5/8"	330'	cem w/ 180 sx
12	6		
13	5 1/2"	3364'	cem w/ 50 sx

ELEVATION 1807' KB

PRODUCTION 22 BOPD & 248 SWPD
Arb 3264-85

FIGURES INDICATE BOTTOM OF FORMATIONS

0	-	75'	Clay & lost Rock
75	-	333'	Shale & Sand
333	-	450'	Shale
450	-	669'	Red Bed
669	-	695'	Anhydrite
695	-	1415'	Shale Shells
1415	-	2000'	Shale & Lime
2000	-	2550'	Shale & Lime
2550	-	2838'	Lime
2838	-	2843'	Shale
2843	-	2858'	Lime Shale
2858	-	2871'	Lime
2871	-	2931'	Shale
2931	-	2946'	Lime Shale
2946	-	3231'	Lime
3231	-	3258'	Conglomerate
3258	-	3270'	Dolomite

3285 No. Log
Total Depth

ELEVATION: 1807 K.B.

FORMATION DATA

Anhydrite	669
Heebner	2838
Brown Lime	2931
Conglomerate	3231
Arbuckle	3258
RTD	3270

SURFACE CASING: Set 8-5/8" at 330' with 180 sacks cement.

PRODUCTION CASING: Set 5 1/2" used casing at 3304' with 50 sbs. cement and 200 gals. latex.

AFFIDAVIT

STATE OF KANSAS
COUNTY OF BARTON) ss.

L. O. Chubb of lawful age, does swear and state that the facts and statements herein contained are true and correct to the best of his knowledge.

