KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU – KANSAS WELL SAMPLE BUREAU
KANSAS GEOLOGICAL SOCIETY BUILDING
508 EAST MURDOCK - WICHITA, KANSAS


COMPANY KATHOL PETROLEUM, INC.

FARM Krier "C" NO. 5

SEC. 30 T. 16 R. 11W
LOC. SE SW SE

TOTAL DEPTH 3188
COMM. 4-18-67 COMP. 4-24-67
SHOT OR TREATED
CONTRACTOR Kathol Petro.
ISSUED 6-24-67

COUNTY Barton
KANSAS



CASING

20	10	
15	8 5/8"	@ 247' w/150 sx
12	6	
13	5	

ELEVATION 1926'KB

PRODUCTION PMP 40 BOPD & 40 BW, LKC 3109-11

FIGURES INDICATE BOTTOM OF FORMATIONS

FROM	TO	
0	247	Soil
247	305	Shale
305	350	Sand
350	550	Shale & Sand
550	630	Red Bed
630	751	Red Bed
751	770	Anhydrite
770	1530	Shale & Shells
1530	1870	Shale & Lime
1870	2130	Lime & Shale
2130	2500	Shale & Shells
2500	2685	Shale & Lime
2685	2775	Lime
2775	2845	Lime
2845	2871	Lime
2871	2885	Lime
2885	2935	Lime
2935	2940	Lime
2940	3000	Shale - Sand
3000	3035	Lime
3035	3090	Lime
3090	3100	Lime
3100	3117	Lime
3117	3157	Lime
3157	3180	Lime
3180	3188	Granite
	3188	T.D.

REMARKS:

Set 247' of 8-5/8" surf. casing with 150 sacks cement, 1% Gel.

TOPS:

Anhydrite	751'
Howard	2593'
Severy	2610'
Topeka	2624'
Heebner	2914'
Toronto	2930'
Douglas Sand	2956-64'
Brown Lime	3006'
Lansing	3024'
Bs. Kansas City	3145'
Granite	3178'
T.D.	3188'

I certify to the best of my knowledge and belief, the above represents a true and accurate driller's log record of the captioned

TOPS: SCOUT

Topeka	2628
Heebner	2914
Toronto	2930
Douglas Sand	2956
B/ " "	2964
Brown Lime	3006
Lansing	3024
Base Kansas City	3145
Granite	3178