

WELL LOG BUREAU KANSAS GEOLOGICAL SOCIETY
508 E. Murdock, Wichita, Kansas

Company NATIONAL COOPERATIVE REFINERY ASS'N.
Farm - Turgeon "B" No. 1

SEC. 9 T. 16 R. 12W
NW NW NW

Total Depth. 3310 = 3301 Straight Hole Corr.
Comm. 4-25-48 Comp. 6-7-48
Shot or Treated.
Contractor.
Issued. 1-7-50

County. Barton

KANSAS



CASING:

10 3/4" 779'
5 1/2" O.D. 3280'

Elevation. _____

Production. 17 BOPD

Figures indicate Bottom of Formations.

cellar	10	lime	2535
shale & shells	40	shale	2550
shale blue	80	lime	2565
shale	220	shale	2580
red rock	270	lime	2585
shale	285	shale	2610
sand	295	shale & shells	2650
shale	305	lime	2795
sand	315	shale	2800
shale	390	lime	2830
sand	415	shale	2835
shale	430	lime	2925
sand	450	shale	2950
shale	475	lime	2965
sand	490	red rock	2970
shale	500	shale	3020
sand	510	lime	3230
red rock	765	shale	3235
gypsum	771	lime	3250
lime	775	shale	3255
anhyd.	790	lime	3282
red rock	995	shale	3289
shale blue	1040	congl	3295
red rock	1090	sand	3310
shale	1195	Total Depth	
salt	1420		
shale	1435		
shale & shells	1530	Tops:	
lime	1600	Anhyd.	775-790
shale	1625	Topeka	2650
lime (Show Gas 1705')	1830	Kansas City	3020
lime brkn	1885	sand	3298
lime	1900		
shale & shells	1940	Water Record:	
shale	1950	6 blrs. wtr. per hr.	285-95
lime	1960	2 " " " "	305-15
red rock	1970	HFW	400
lime	2037	8 " " " "	450
red rock	2050	HFW	475-85
lime	2091	2 " " " "	1820
shale	2095	1 " " " "	2065
lime	2130	3 1/2 " " " "	2460
shale	2135	1 1/2 " " " "	2735
red rock	2145	1 " " " "	3040
lime	2165	HFW	3105
shale	2170	2 " " " "	3155
lime	2220	1 1/2 " " " "	3195
shale	2240		
lime	2245		
shale & shells	2270		
shale & lime	2345		
shale	2405		
shale & lime	2460		
shale	2495		
lime	2500		
shale	2510		
lime	2520		
shale	2530		