

CLAMPITT AND SEANEY.
 Schauf No. 1.

SEC. 1 T. 16 R. 12 W.
 CSL SE SW


Total Depth. 3394.
 Comm. 10-29-39 Comp. 11-3-39
 Shot or Treated. 72 shots 2880-2900
 Contractor. 12 shots 3371-3376
 Issued. 11-11-39

County Barton.

CASING.

12 1/2" 40

6 1/2" 3394'



Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

surface	14	lime	2992
lime	24	shale	2997
shale and lime	401	smell oil	2997-3000
shale and shells	420	lime	3006
sand	495	shale	3031
shale	525	shale and lime	3051
red rock	553	lime	3083
shale shells	740	cored and reamed	3083-3090
lime anhydrite	770	lime	3123
shale and shells	940	shale and lime	3142
anhydrite	990	cored	3142-56
shale and shells	1280	lime	3184
shale and salt	1390	lime shale	3222
salt shale and shells	1445	lime	3251
lime and shale	1555	shale	3268
lime	1655	lime	3276
shale and lime	1740	lime & shale	3300
lime	1758	shale	3309
shale	1770	lime	3325
lime	1795	cong. and red	
shale and shells	1820	beds	3332
lime	1830	cong. shale	3357
shale and lime	1892	shale	3359
pyrite	1894	coring	3363-68
lime	1930	lime	3370
shale	1938	coring	3368-70 stain of oil
lime	2075	sand	3374
shale and lime	2105	show oil	3373-3374
lime	2155	lime	3394
shale	2160	Total Depth.	
lime	2217		
shale and lime	2280	Top Topeka	2697
lime	2292	Top Kansas City	3051
shale	2300		
lime	2340		
shale and shells	2375		
shale	2430		
lime	2440		
shale and shells	2490		
lime and shale	2555		
shale	2603		
lime	2615		
shale and shells	2635		
lime	2654		
shale	2678		
shale shells lime	2710		
lime	2753		
shale lime shells	2769		
pyrite	2770		
sd lime	2780		
shale lime shells	2794		
lime	2890		
lime broken sh oil	2901		
lime	2943		
broken lime	2950		
shale	2969		