

3-16-5W

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas


Company- CURRIER & KEYS
Farm- Martin No. 4

SEC. 3 T. 16 R. 3W
C SW SE

Total Depth. 3485
Comm. 5-24-53 Comp. 6-6-53
Shot or Treated.
Contractor. Sterling Drilling Co.
Issued. 7-25-53

County Saline

KANSAS



Elevation. 1306 DF

Production. Pump 30 BO, 10% W

CASING:

8 5/8 set at 325' w/ 250 sx cement
5 1/2 set at 3470' w/ 10 sx cement

Figures indicate Bottom of Formations.

clay, shale & shells	325
lime	885
shale	1120
shale & shells	1440
shale	1665
lime	1945
shale & lime	2500
lime	2590
shale & lime	2765
shale	2810
Mississippi lime	2990
lime	3045
shale	3180
lime & shale	3255
shale	3278
Maquoketa lime	3300
lime	3420
lime & shale	3470
shale	3474
sand	3477
shale	3479
sand (HFW)	3485
Total Depth	
TOPS; R.B.	
Maquoketa shale	3218
Maquoketa dolomite	3277
Viola lime	3334
Simpson sand	3474