10-16-3W


WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
Wichita, Kansas

Company. CURRIER & KEYS
Farm. G. Johnson No. 1

SEC. 10 T. 16 R. 3W
NE/c NW

Total Depth. 3664½
Comm. 6-8-49 Comp. 8-3-49
Shot or Treated. 1000 gals.
Contractor. E. K. Carey Contractor
Issued. 12-17-49

County. Saline
KANSAS



Elevation. 1306 Ind.

CASING:
8" set @ 305'
5" set @ 3353'

Production. 42 Bbls.

Figures Indicate Bottom of Formations.

Shale	40
Sand & shale	70
Lime & shale	135
Shale & shells	166
Reamed	161
Shale	270
Shale & shells	300
Cement & plug	305
Anhydrite lime	330
Lime & breaks	350
Lime & sand	855
Shale	900
Shale & shells	1120
Shale & lime	1630
Lime	2010
Lime & shale	2105
Lime	2305
Lime & shale	2634
Shale	2805
Chat	2854
Mississippian	2888
Mississippi lime	2940
Lime	2990
Ream	2975
Lime	3021
Shale & lime	3164
Shale	3288
Lime	3320
Rotary T.D.	3360 D.F.

Cable Tools

Cement	3361
Soft lime oil	3364
Lime harder	3664½
3 BWPD	

Total Depth

P. B. to 3363½, acidized w/1000 gals acid.
Initial Production 42 BOPD