

PRYOR & LOCKHART, INC.
Stratmann No.8.

SEC.2 T.17 R.10W
CSL NW NE

Total Depth. 3309'
Comm. 6-13-41 Comp. 7-3-41
Shot or Treated.
Contractor.
Issued. 8-23-41

County. Ellsworth



CASING:
10" 243'
7" 3281'

Elevation.

Production. Pot.217 B.

Figures Indicate Bottom of Formations.

cellar	6	lime	3283
surface clay	45	Cable	
sand & clay	85	conglomerate	3286
sand	120	lime	3307
shale & shells	243	lime sdy	3309
shale	390	Total Depth.	
sand	450		
shale	550		
red bed	576	sh oil 3306-07	
anhydrite	590	slight inc.in	
lime	599	fillup 3308-09	
shale	995		
salt	1230	Tops:	
shale & shells	1250	Conglomerate	3270
lime brkn	1320	Arbuckle	3279
shale & lime	1455		
shale	1490		
lime	1505		
red bed	1535		
shale & lime	1622		
shale	1635		
sand	1655		
lime	1665		
shale & lime	1720		
lime	1750		
shale & lime	1770		
lime brkn	1780		
red rock	1790		
shale & lime	1810		
shale	1840		
lime	1860		
shale & shells	1910		
lime	1928		
shale	1935		
lime	1980		
shale & lime	2005		
shale & shells	2265		
lime	2295		
shale	2340		
lime	2360		
shale	2365		
lime	2373		
shale & shells	2415		
lime	2425		
shale & shells	2485		
lime	2495		
lime brkn	2530		
lime	2550		
shale	2570		
lime & shale brks	2610		
shale	2615		
lime	2807		
shale	2827		
lime & shale brks	2862		
shale	2920		
lime brkn	2945		
lime	3144		
lime brkn	3160		
lime	3251		
brkn lime & shale	3269		
shale	3279		