


EARL F. WAKEFIELD.
Janssen "A" No. 1

SEC. 29 T. 17 R. 10 W.
CNW NE

Total Depth. 3343
Comm. 4-2-42 Comp. 4-16-42
Shot or Treated.
Contractor. Earl F. Wakefield.
Issued. 5-23-42

County Ellsworth.



CASING.

85/8" 122'

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

surface clay	83	lime with shale streaks	2779
sand	103	lime and shale streak	2828
shale	111	sdv hard lime	2837
shale and shells	365	lime soft	2903
red bed	569	shale	2959
anhydrite	588	lime	2965
shale red	616	lime broken	2981
shale and shells	1015	lime	3046
salt and shale	1280	lime and shale	3064
shale	1298	lime	3070
shale and shells	1312	lime soft	3099
lime	1340	lime	3101
shale and shells	1355	lime hard	3120
shale	1365	lime with shale streak	3134
lime broken	1435	lime hard	3152
shale and shells	1505	lime	3225
lime broken	1585	lime with shale streak	3253
shale	1595	lime and shale	3263
lime broken	1680	conglomerate	3279
shale	1690	conglomerate cherty	3293
lime	1712	Arbuckle	3295
shale and lime	1770	corrected to derrick floor.	
lime	1820	Standardized	
shale and shells	1935	lime	3343
lime	1950	Total Depth.	
lime broken	2015	Water shows 3327-3330	
lime	2035	Increase in water 3333	
sdv shale	2052	Top Arbuckle 3291 Corr.	
shale & lime shells	2145		
lime broken	2205		
shale	2225		
lime sdv	2280		
shale	2302		
lime	2322		
shale and shells	2373		
lime	2388		
shale and shells	2394		
shale	2400		
lime broken	2425		
shale and lime	2462		
shale	2510		
lime	2530		
shale	2562		
lime	2570		
shale and shells	2590		
lime	2630		
lime broken	2654		
lime	2715		
lime broken	2750		