WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
412 Union National Bank Bldg, Wichita, Kansas.

THE TEXAS COMPANY.
H.Disque No. 9

SEC. 3 T. 17 R. 11W.
SE NW SW SW
397' f WL 739' f SL SW¼

Total Depth. 3372
Comm. 1-31-41 Comp. 2-12-41
Shot or Treated.
Contractor. Helmerich and Payne, Inc.
Issued. 4-5-41

County Barton.



Rotary 3372

CASING.

10 3/4" 283' cement.

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

shells and shale	180
shale and sand	370
shale and red bed	620
anhydrite	645
shale	695
lime hard	730
shale and shells	1100
salt and shale	1170
shale and shells	1385
shale and lime	1725
shale	1805
shale and lime	1890
lime	1950
shale and lime	2280
shale	2350
broken lime	2353
shale and lime	2605
lime	2915
lime and shale	3035
lime	3135
shale and lime	3210
lime	3305
conglomerate	3307
lime	3351
conglomerate	3355
chorty lime	3357
lime	3372
Total Depth.	

Plugged well with cement and mud from 3372 to 400' and placed permanent bridge at 400' and cemented to 385' and mud to 14' and cement to 8' and mud to surface. 283' of 10 3/4" OD surface pipe left in hole.