WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita,Kansas

LAUCK & MONCRIEF ET AL
Riemann No. 1.

SEC.10 T.17 R. 11 W
NWc SW

Total Depth. 3317'
Comm. 10-1-41 Comp. 10-25-41
Shot or Treated.
Contractor.
Issued. 12-27-41

County. Barton



CASING:
10" 138' Cem.
5" 3294' Cem.

Elevation.

Production. Pot.402 B.

Figures Indicate Bottom of Formations.

surface	30	lime & green shale	3299
shale sdy	70	slight inc. in oil	
shale & shells	460	lime medium	3301
anhydrite	470	100' oil	
shale & shells	525	lime medium	
shale & red rock	675	150' oil	
shale & shells	750	300' oil in 17½ hrs	
shale & red rock	810	lime,slight inc.	3307
shale & shells	945	lime med,good inc.	3309
shale	982	lime hrd	3310
shale & shells	1090	1300' oil	
salt	1280	lime hrd	3314
salt & shale	1295	1900' oil	
shale	1340	lime sft	3315
lime brkn	1580	best pay 2500 oil	
sand	1590	swb 7½ Bbls hr.80' off btm	
lime	1655	10-23-41 temp.Tot.51 B.	
lime sdy	1675	Acidized 500 Gals.	
lime	1700	(acidized 18 hrs)	
lime sdy	1720	swb 1 BPH	
lime	1770	lime,sft,good sat.	3316½
shale	1812	swb 31¼ Bbls in 5 hrs	
lime brkn	1860	off btm	
shale	1870	Acidized 1000 Gals.thru	
lime brkn	1960	osg	
shale & shells	1970	Swb 10 Bbls hr off btm	
lime brkn	2120	lime hrd	3317
shale & shells	2305	Acidized 3000 Gals.	
shale	2355	pmp 12½ Bbls per hr	
shale & shells	2590	Total Depth.	
shale & lime	2640		
lime	2660		
shale & lime	2695	Top Arbuckle 3294 Corr.	
lime sdy	2710		
lime	2737		
lime sft	2744		
lime	2852		
lime sft	2880		
lime	2935		
shale	3010		
lime	3117		
lime porous	3147		
lime	3155		
lime brkn	3180		
lime	3200		
lime porous	3208		
lime	3294		
Arbuckle lime	3295		
Derrick floor			
Top Arbuckle 3293			
Total depth 3294			
Standardized			
Rotary T.D.3294-3295 cable tools			
Top Arbuckle Corr.	3294		
lime & chert	3296		
show free oil			
lime hrd	3297		
free oil			