WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
412 Union National Bank Bldg, Wichita, Kansas.

SKELLY OIL CO.
H.W.Armbrust No. 1

SEC. 21 T. 17 R. 11 W.
NEc NW
330' f NL 330' f EL NW¼

Total Depth. 3340 P.B. 3326
Comm. 2-21-42 Comp. 3-6-42
Shot or Treated.
Contractor. Bodine Drilling Co.
Issued. 5-2-42

County Barton



CASING. Rotary.

8 5/8" 319' Cemented.
5½" 3336' Cemented.

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

surface clay and sand	165	
red rock	345	
shale, shells and pyrites of iron	450	
red bed	650	
lime	690	
red rock	750	
shale	1125	
shale and salt	1250	
shale and shells	1360	
lime	1470	
sdy lime	1550	
lime	1590	
shale	1610	
lime	1655	
sdy lime	1815	
lime and shale	2040	
shale	2050	
shale and lime	2265	
shale and shells	2555	
shale	2600	
shale and lime	2700	
lime	2750	
shale and lime	2805	
sdy lime and shale	2870	
lime and shale	2910	
lime	2925	
shale blk	3000	
lime and shale	3006	
med hard grey and brown oolitic lime	3014	porous, slight saturation.
lime	3034	
med hard grey and brown oolitic lime	3041	porous and stained.
lime and shale	3091	
very soft grey oolitic lime	3128	porous, no oil or gas saturation.
lime	3150	
broken lime	3200	
lime and shale	3245	
lime dark grey	3268	
white & red chert & shale	3280	
chert, shale and sand conglomerate	3330	
chert and conglomerate	3332	
white dolomite	3340	Porous, water saturated.
Total Depth P.B. 3326		

3-13-42 perforated 5½"casing by Lane Wells with 48 holes 3027-3040½ no shows.
48 holes 3004-3013 no shows.

3-14-42 1000 gal acid 3027-3040½
3-14-42 1000 gal acid 3004-3013

Top Lansing 3003
Congl. 3268
Arbuckle 3332