WELL LOG BUREAU — KANSAS GEOLOGICAL SOCIETY
508 E. Murdock, Wichita, Kansas

Company. EL DORADO REFINING CO.
Farm. Ehler "B" No. 6

SEC. 12 T. 17 R. 11W
SE SE SW

Total Depth. 3580
Comm. 6-23-50 Comp. 7-3-50
Shot or Treated.
Contractor. Sterling Drlg.
Issued. 9-2-50

County. Barton
KANSAS



Elevation. 1890 DF

Production. 40 bbls oil, 25% wtr.

CASING:
8 5/8# 320' cem w/150 sx.
5½" OD 3412.01' cem w/200 sx.

Figures Indicate Bottom of Formations.

| | |
|---|---|
| surface | 318 |
| shale | 370 |
| red bed, shale | 660 |
| anhyd. | 695 |
| shale, shells | 900 |
| shale, salt | 1390 |
| lime, shale | 1645 |
| lime | 2050 |
| lime, shale | 2675 |
| lime | 2902 |
| shale | 3025 |
| lime | 3295 |
| conglomerate, shale | 3345 |
| conglomerate, chert | 3366 |
| arbuckle lime | 3425 |
| lime | 3485 |
| cherty lime | 3520 |
| lime sdy | 3538 |
| granite wash | 3580 |
| total depth | |

Tops: DF

| | |
|---|---|
| Lansing | 3034 |
| Cong. | 3316 |
| Arbuckle | 3362 |
| Reagan sand | 3470 |
| Pre-cambrian | 3536 |

DST 3105-12, open ½ hr, rec. 850'
gas & 55' very heavily O & Gas cut mud.
BHP 570# plus or minus.
Perf. (12) 3106-09, SSO, 500 acid. 10-15 GOPH.
700' FIH/12 hrs, ⌀ 25 BO and 50 BW/20 hrs.
Tested 8 BO & 10 BW/12 hrs, 40.6 gr. oil.