

WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY

508 East Murdock,

Wichita, Kansas

Company- HUGOTON PROD. CO.  
 Farm- H. T. Floyd No. 1

SEC. 19 T. 17 R. 29W  
 NW NE SW

Total Depth. 4705

Comm. 4-1-52

Shot or Treated.


Contractor. M. B. Armer

Issued. 7-19-52

Comp. 5-7-52

County Lane

KANSAS



Elevation. 2834

Production. IPP 160 BO NW

CASING:

8 5/8" 236' cem. w/200 sx  
 5 1/2" 4534' cem. w/200 sx

Figures Indicate Bottom of Formations.

clay	45
sand	60
shale & clay	85
sand & gravel	210
shale & shells	400
sandy shale	450
shale & shells	660
sand	825
sandy shale	960
shale	1000
sand	1140
shale & shells	1460
sandy shale	1660
sandy shale & shells	1680
sandy shale	2000
sandy shale & red bed	2219
anhydrite	2246
shale, red bed & shells	2460
shale & shells	2875
shale	2975
lime & shale	3120
shale	3160
shale & lime	3555
lime	3610
lime & shale	3750
lime	3810
lime & shale	3845
lime	4211
lime & shale	4230
lime	4260
lime & shale	4295
lime	4320
lime & shale	4390
lime	4423
lime & shale	4545
<del>shale &amp; sand</del>	4568
lime & shale	4590
lime	4705 RTD
Total Depth	

Tops:	
Anhydrite	2220
Heebner	3916
Lansing-K. C.	3954
Marmaton	4381
Miss.	4599

Perf. were made from 4333' to 4352' and from 4397 to 4426'.  
 A Baker Bridge Plug was set at 4375'.  
 4340' of 2 1/2" tubing was set and 4320' of 3/4" sucker-rods were run.