


HOLLOW DRILLING CO., INC.  
 Janzen No. 1,

SEC. 18 T. 17 R. 9W.  
 CSL SW SE

Total Depth. 3259  
 Comm. 1-30-40 Comp. 2-28-40  
 Shot or Treated. 1000 gal.  
 Contractor.  
 Issued. 4-27-40

County Ellsworth.



CASING.

85/8" 208'  
 5" 3251'

Elevation.

Production. Pot. 7070 B.

Figures Indicate Bottom of Formations.

|                        |           |
|------------------------|-----------|
| sand and lime shells   | 120       |
| shaly shale and shells | 205       |
| red rock               | 501       |
| anhydrite              | 519       |
| red rock               | 800       |
| lime                   | 850       |
| lime and shale         | 905       |
| shale                  | 975       |
| salt                   | 1220      |
| shale and shells       | 1235      |
| shale                  | 1265      |
| lime                   | 1295      |
| shale and shells       | 1365      |
| lime                   | 1390      |
| shale and shells       | 1605      |
| lime                   | 1795      |
| lime and shale         | 2200      |
| shale                  | 2285      |
| lime and shale         | 2375      |
| shale                  | 2430      |
| lime                   | 2781      |
| shale                  | 2784      |
| lime                   | 2795      |
| shale                  | 2805      |
| lime                   | 2810      |
| shale                  | 2866      |
| lime and shale         | 2900      |
| lime                   | 2910      |
| lime and shale         | 2925      |
| lime                   | 3007      |
| oolitic lime & shale   | 3024      |
| conglomerate           | 3043      |
| shale green            | 3246      |
| shale green & sand     | 3251      |
| Arbuckle dolomite      | 3259 Oil. |
| Total Depth.           |           |