


PRYOR & LOCKHART, INC.
Schroeder No. 2.

SEC. 30 T.17 R.9 W
CNE SE NW

Total Depth. 3283'
Comm. 4-18-43 Comp. 5-1-43
Shot or Treated.
Contractor.
Issued. 5-15-43

County. Ellsworth



CASING:
10" 218' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

sand	70
sand & shale	218
shale	340
red rock	485
anhydrite	505
shale	618
shale & shells	960
salt	1170
shale	1200
lime & shale bks	1275
lime & shale	1305
shale	1370
lime	1390
shale	1410
shale & lime	1505
sand & shale	1515
lime & shale bks	1540
sdv lime	1575
lime	1625
lime brkn	1700
shale	1730
lime	1760
lime & shale bks	2092
lime	2140
shale	2225
lime	2245
shale	2333
shale & shells	2418
lime	2635
lime brkn	2655
lime	2748
lime cherty	2785
lime	2810
shale	2887
shale & lime	2960
lime	3091
lime brkn	3120
lime	3130
3137 equals 3130 Corr.	
lime brkn	3150
lime	3195
shale	3230
sand	3257
shale & lime shells	3272
lime Arbuckle	3283
Total Depth.	

Top Arbuckle 3272