

Location. N.W.c-S.W.

DEEPENING RECORD.

Sec. 26 T. 18 R. 10W

Casing Record.

County, Rice

133/8440 10" 1765 Farm. Godfrey
 20" 8" 2470 Company. Slick-Pryor & Lockhart
 15" 183 65/8" 2932 Contr.
 12" 53/16" 2 Comm. 5-13-33

No. 1

Comp. 7-26-33



Sci. Tops.
 Cong 3221
 Sil 3224

Total Depth. 3367 Shot Quarts Between.

Correspondence Regarding This Well Should Be Referred To.

Elevation. 1750

Figures Indicate Bottom of Formations.

Initial Production, Dry TD. 3328

Date Issued. 11-18-35

Now Prod. - pump 120 B. TD 3367

Formation	Depth	Formation	Depth	Formation	Depth
Cellar	12	Shale	1775	Formation	
Yellow clay H.F.W.	80	Lime	1790	Line sandy	2720
Sand	155	Red rock	1805	Line	2775
Shale Blue	158	Lime	1845	Shale	2780
Shale dark	185	Shale	1850	Lime	2795
8 B.W.P.H. 180-2 00		Lime	1860	Shale	2805
Line	200	Shells & Shale	1880	1 1/2 B.W. 2805-	
Shale	245	Lime	1895	Sdy Line	2820
Red Rock	425	Red rock	1905	Shale	2860
Shale red	430	2 B.W. 1910-1920		Line	2865
Lime Anhydrite	440	Lime	1970	Shale	2880
Lime	450	Shale	1975	Lime	2895
Red Rock	525	Lime	1980	Show gas 2895-2900	
Shale brown	600	Shale	1985	Sdy line	2900
Red rock	670	Lime	1990	Gas	2939
Shale brown	700	Cave		Line 2932- equals	2939
Shale blue	750	Shale blue	2015	Lime H.F.W.	2980
Red rock	760	Shale black	2020	Sdy line	2990
Shale brown	800	Lime	2030	Swabed hole dry	3035
Shale blue	870	Bad cave		Line	3070
Lime	875	Shale	2055	Show oil 3070-75	
Shale blue	910	Lime	2065	Line sandy	3075
Salt	1140	Shale	2070	Lime	3145
Shale blue	1165	Red rock	2080	Shale	3150
Lime	1175	Shale blue	2095	Lime	3165
Shells & Shale	12 20	Lime	2105	Shale white	3170
Lime	1230	1 1/2 B.W. 2120-2130		Lime	3185
Shale	1235	Shale	2120	Line	3220
Lime	1265	Sandy lime	2130	Shut down 2 hrs. ran bailer	
Line	1275	Lime	2140	made 4 gal. oil & 2 gal	
Shale & Shells	1300	Shale	2150	water in 2 hrs.	
Red Rock	1315	Lime	2155	Conglomerate	3250
Shale blue	1325	Shale	2185	Lime	3236
Lime	1340	Cave		Washed free oil 3234-36	
Lime & shale	1365	Lime	2200	" " " 3236-38	
Lime	1395	Shale	2245	Line	3238
Shale	1405	Lime	2265	Hole filled up 500-600	
Red Rock	1425	Shale	2270	feet oil in 3 hours	
Show gas	1430	Lime	2275	Sand 3240-3237-8	
Lime	1450	Shale	2280	Sand	3263
Shale	1455	Lime	2285	Washing some oil 3245-47	
Line broken	1520	Shale	2295	Lime	3323
Lime	1540	Lime	2315	Sand	3328
5 B.W. 1540-1555		Shale & Shells	2325	Total Depth	
Sandy lime	1555	Lime	2335	Underreamed 8 1/2 to 2496	
Lime	1575	Shale	2350	" 65/8 3010	
Shale brown	1585	Lime	2355	3240 equals 3237+8"	
Lime	1610	Shale sandy	2375		
Shale green	1615	Shale	2395		
Lime	1635	Lime	2420		
Shale	1650	Shale	2425		
Lime	1655	Lime	2450		
Red rock	1670	Shale	2455		
Lime	1680	lime	2460		
Shells	1690	Shale	2465		
Red rock	1695	Sand	2470		
Lime	1710	Sdy lime	2490		
Red rock	1725	5 B.W. 2535			
Lime	1735	Lime	2610		
Shale	1740	Shale	2615		
Lime	1745	Lime	2715		
Shale	1750	1 B.W. & show oil	2715		
Line broken	1760				
Lime	1770				

1750
 1425
 +325

2880
 1750
 1130

DEEPENING RECORD.

Old T.D. 3328

Conn. 10-4-33 Comp. 11-1-33
 Prod. Pump 120 bbls.

sand hard 3328- 3337
 quartzite 3367 TT

P.B. to 3252 corrected to
 3260. and shot 30 qts 53/16 3238