


SLICK PRYOR AND LOCKHART.
Orth No. 3

SEC. 27 T. 18 R. 10W.
SWc NE

Total Depth. 3178
Comm. 4-20-35. Comp. 7-15-35
Shot or Treated.
Contractor.
Issued. -9-7-35

County. Rice



Set Tops
None

CASING.

20" 166' 10" 1245' UR 1602'
15 1/2" 441' 8" 2468' UR 2722'
133/8" 915' 65/8" 3035 UR 3142

Elevation. 1751

Production. 15,000,000 G.

Figures Indicate Bottom of Formations.

cellar	12	shale blue	1280	hole caving some.	
yellow clay	35	shale brown	1290	more gas 2025-30	
yellow clay	75	lime	1335	shale light	2075
gravel	85	shale brown	1340	lime	2080
clay	95	lime	1345	shale	2115
sand	110	shale	1350	shale dark	2160
sand	160	lime	1380	lime	2170
slate blue	185	red rock	1395	shale dark	2225
sdv shale	200	lime soft	1425	lime	2240
slate blue	205	lime hard	1430	shale	2245
14 BWPBR 185-200		lime	1435	lime	2250
shale blk	230	shale grey	1450	shale shells	2275
sand	235	lime soft grey	1510	shale light	2285
shale	240	Show of gas 1360-1370		lime shells&shale	2300
sand hard & iron	240	more gas from 1405-1410		shale dark	2320
sand hard	255	1 BW 1490		shale light	2330
sand hard	260	lime	1525	sdv shale	2345
red rock	295	lime soft	1540	shale	2365
red rock	355	lime hard	1550	lime	2370
6 BW 240-250		shale red	1562	shale	2380
red rock	405	lime soft	1570	lime	2390
shale red	420	lime	1575	shale dark	2400
shale red	437	shale	1596	lime	2415
lime	441	lime hard	1602	lime	2420
lime	455	5 BWPBR 1540.		shells & shale	2430
shale brown	485	lime	1605	sdv shale	2450
shale brown	495	shale	1610	4 BW 2330-2345	
red rock	520	lime	1615	HFW 2430-40	
shale brown	540	shale	1625	sdv shale	2453
red rock	600	shale blue sdy	1640	lime	2455
shale red	690	shale brown	1645	shale	2458
red rock	700	lime	1650	lime	2468
shale blue	735	shale light	1660	lime	2555
shale blue	750	lime	1665	shale 1/2 BW 2495-2505	2560
shale brown	775	shale brown	1680	lime	2565
shale brown & grey	810	lime	1685	lime	2580
shale light	825	shale light	1695	shale	2585
shale blue	885	shale brown	1715	lime	2590
shale blue	902	shale brown	1717	lime	2600
sand	910	lime hard	1750	HFW 2595-2600	
sand	915	lime soft	1760	hole caving 2555-60	
HFW 910		lime hard	1770	and 2580-85	
hole caving.		red rock	1775	HFW 2595-2600	
salt	935	red rock	1785	lime	2616
salt	1127	lime	1815	shale	2622
shale grey	1137	Gas at 1790		lime	2628
salt	1150	lime	1830	lime hard	2665
shale blue	1160	shale light	1840	lime soft	2680
lime	1170	lime	1845	lime	2695
shale blue	1180	shale light	1860	show oil and gas 2665-70	
shale and shells	1190	shale brown	1870	hole filled up 350' with	
shale	1195	lime	1875	oil in 2 hours 2670-75	
shale and shells	1210	lime 1BW 1890-98	1877	1500 ft oil in hole.	
shale blue	1220	red rock	1890	lime	2765
lime	1230	lime hard	1910	showing oil & wtr.	
lime	1240	lime shells and shale	1965	shale	2770
shale blue	1245	1/2 BW 1877-90		lime soft	2775
lime	1250	shale	1995	shale grey	2805
shale	1255	shale and shells	2005	bailed hole dry 2740	
lime	1265	shale shells	2050	1/2 BW 2770-75	
		shale	2070	OVER	

