




11-18s-15w

15-009-25309-00-00

KGS

	DRILL STEM TEST REPORT																																														
MA OIL OPERATIONS INC 8411 PRESTON RD STE 800 DALLAS, TX 75225+5520 ATTN: KITT NOAH	MANETH #1 11-18S-15W BARTON Job Ticket: 16693 DST#: 1 Test Start: 2009.03.13 @ 03:50:00																																														
GENERAL INFORMATION:																																															
Formation: LANSING KC A-C Deviated: No Whipstock: ft (KB) Time Tool Opened: 05:52:55 Time Test Ended: 10:45:54		Test Type: Conventional Bottom Hole (Initial) Tester: JARED SCHECK Unit No: 3320 - 35 - GB																																													
Interval: 3307.00 ft (KB) To 3332.00 ft (KB) (TVD) Total Depth: 3332.00 ft (KB) (TVD) Hole Diameter: 6.88 inches Hole Condition: Fair		Reference Elevations: 2001.00 ft (KB) 1993.00 ft (CF) KB to GR/CF: 8.00 ft																																													
Serial #: 27799 Inside																																															
Press@RunDepth: 187.65 psia @ 3327.00 ft (KB) Start Date: 2009.03.13 End Date: 2009.03.13 Start Time: 03:50:25 End Time: 10:45:55		Capacity: 5000.00 psia Last Calib.: 2009.03.13 Time On Btm: 2009.03.13 @ 05:52:25 Time Off Btm: 2009.03.13 @ 08:57:25																																													
TEST COMMENT: 45/INITIAL OPEN: STRONG BLOW BUILT BOTTOM OF BUCKET IN 4 MINUTES 45/INITIAL SHUT-IN: 6 INCH BLOW BACK 45/FINAL OPEN: STRONG BLOW BUILT BOTTOM OF BUCKET IN 4 MINUTES GAS TO SURFACE 15 MINUTES INTO OPEN 45/FINAL OPEN: 4 INCH BLOW BACK																																															
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4" style="text-align: center;">PRESSURE SUMMARY</th> </tr> <tr> <th>Time (Min.)</th> <th>Pressure (psia)</th> <th>Temp (deg F)</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>0</td><td>1652.24</td><td>91.83</td><td>Initial Hydro-static</td></tr> <tr><td>1</td><td>39.62</td><td>91.91</td><td>Open To Flow (1)</td></tr> <tr><td>46</td><td>116.61</td><td>96.12</td><td>Shut-In (1)</td></tr> <tr><td>91</td><td>937.05</td><td>100.08</td><td>End Shut-In (1)</td></tr> <tr><td>92</td><td>124.36</td><td>100.11</td><td>Open To Flow (2)</td></tr> <tr><td>136</td><td>187.65</td><td>102.90</td><td>Shut-In (2)</td></tr> <tr><td>184</td><td>918.83</td><td>105.12</td><td>End Shut-In (2)</td></tr> <tr><td>185</td><td>1577.92</td><td>105.15</td><td>Final Hydro-static</td></tr> </tbody> </table>		PRESSURE SUMMARY				Time (Min.)	Pressure (psia)	Temp (deg F)	Annotation	0	1652.24	91.83	Initial Hydro-static	1	39.62	91.91	Open To Flow (1)	46	116.61	96.12	Shut-In (1)	91	937.05	100.08	End Shut-In (1)	92	124.36	100.11	Open To Flow (2)	136	187.65	102.90	Shut-In (2)	184	918.83	105.12	End Shut-In (2)	185	1577.92	105.15	Final Hydro-static				
PRESSURE SUMMARY																																															
Time (Min.)	Pressure (psia)	Temp (deg F)	Annotation																																												
0	1652.24	91.83	Initial Hydro-static																																												
1	39.62	91.91	Open To Flow (1)																																												
46	116.61	96.12	Shut-In (1)																																												
91	937.05	100.08	End Shut-In (1)																																												
92	124.36	100.11	Open To Flow (2)																																												
136	187.65	102.90	Shut-In (2)																																												
184	918.83	105.12	End Shut-In (2)																																												
185	1577.92	105.15	Final Hydro-static																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3" style="text-align: center;">Recovery</th> </tr> <tr> <th>Length (ft)</th> <th>Description</th> <th>Volume (bbl)</th> </tr> </thead> <tbody> <tr><td>60.00</td><td>W CUT OM 5%O 5%M 90%W</td><td>0.84</td></tr> <tr><td>120.00</td><td>WM CUT O 5%W 5%M 90%O</td><td>1.68</td></tr> <tr><td>60.00</td><td>WM CUT GO 5%W 5%M 30%G 60%O</td><td>0.84</td></tr> <tr><td>60.00</td><td>WM CT GO 5%W 5%M 35%G 55%O</td><td>0.84</td></tr> <tr><td>60.00</td><td>GO CT MW 10%G 10%W 10%M 70%O</td><td>0.84</td></tr> <tr><td>20.00</td><td>GO CUT MW 5%G 20%W 20%M 55%O</td><td>0.28</td></tr> </tbody> </table>		Recovery			Length (ft)	Description	Volume (bbl)	60.00	W CUT OM 5%O 5%M 90%W	0.84	120.00	WM CUT O 5%W 5%M 90%O	1.68	60.00	WM CUT GO 5%W 5%M 30%G 60%O	0.84	60.00	WM CT GO 5%W 5%M 35%G 55%O	0.84	60.00	GO CT MW 10%G 10%W 10%M 70%O	0.84	20.00	GO CUT MW 5%G 20%W 20%M 55%O	0.28	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4" style="text-align: center;">Gas Rates</th> </tr> <tr> <th></th> <th>Choke (inches)</th> <th>Pressure (psia)</th> <th>Gas Rate (Mcf/d)</th> </tr> </thead> <tbody> <tr><td>First Gas Rate</td><td>0.25</td><td>2.50</td><td>3.97</td></tr> <tr><td>Last Gas Rate</td><td>0.25</td><td>2.50</td><td>3.97</td></tr> <tr><td>Max. Gas Rate</td><td>0.25</td><td>2.50</td><td>3.97</td></tr> </tbody> </table>		Gas Rates					Choke (inches)	Pressure (psia)	Gas Rate (Mcf/d)	First Gas Rate	0.25	2.50	3.97	Last Gas Rate	0.25	2.50	3.97	Max. Gas Rate	0.25	2.50	3.97
Recovery																																															
Length (ft)	Description	Volume (bbl)																																													
60.00	W CUT OM 5%O 5%M 90%W	0.84																																													
120.00	WM CUT O 5%W 5%M 90%O	1.68																																													
60.00	WM CUT GO 5%W 5%M 30%G 60%O	0.84																																													
60.00	WM CT GO 5%W 5%M 35%G 55%O	0.84																																													
60.00	GO CT MW 10%G 10%W 10%M 70%O	0.84																																													
20.00	GO CUT MW 5%G 20%W 20%M 55%O	0.28																																													
Gas Rates																																															
	Choke (inches)	Pressure (psia)	Gas Rate (Mcf/d)																																												
First Gas Rate	0.25	2.50	3.97																																												
Last Gas Rate	0.25	2.50	3.97																																												
Max. Gas Rate	0.25	2.50	3.97																																												

 KANSAS CORPORATION COMMISSION
 MAY 12 2009
 RECEIVED



DRILL STEM TEST REPORT

MAI OIL OPERATIONS INC

MANETH #1

8411 PRESTON RD STE 800
DALLAS, TX 75225+5520

11-18S-15W BARTON

Job Ticket: 16694

DST#: 2

ATTN: KITT NOAH

Test Start: 2009.03.13 @ 19:10:00

GENERAL INFORMATION:

Formation: **LANSING KC E-F**

Deviated: No Whipstock ft (KB)

Time Tool Opened: 20:42:55

Time Test Ended: 02:13:20

Test Type: Conventional Bottom Hole (Initial)

Tester: JARED SCHECK

Unit No: 3320- 35 - GB

Interval: **3363.00 ft (KB) To: 3390.00 ft (KB) (TVD)**

Total Depth: 3390.00 ft (KB) (TVD)

Hole Diameter: 6.88 inches Hole Condition: Fair

Reference Elevations: 2001.00 ft (KB)

1993.00 ft (CF)

KB to GR/CF: 8.00 ft

Serial #: **27799** Inside

Press@RunDepth: 127.83 psia @ 3385.00 ft (KB)

Start Date: 2009.03.13 End Date: 2009.03.14

Start Time: 19:10:25 End Time: 02:13:19


Capacity: 5000.00 psia

Last Calib.: 2009.03.14

Time On Btm: 2009.03.13 @ 20:41:55

Time Off Btm: 2009.03.14 @ 00:04:55

TEST COMMENT: 45/INITAL OPEN:STRONG BLOW BOTTOM OF BUCKET IN 2 MINUTES
45/INITAL SHUT IN:6 INCH BLOW BACK
45/FINAL OPEN:STRONG BLOW BUILT BOTTOM OF BUCKET IN 2 MINUTES
45/FINAL SHUT IN:BLOW BACK BOTTOM OF BUCKET GAS TO SURFACE IN SHUT IN



PRESSURE SUMMARY

Time (Min.)	Pressure (psia)	Temp (deg F)	Annotation
0	1717.09	91.84	Initial Hydro-static
1	51.80	92.11	Open To Flow (1)
48	89.37	94.53	Shut-In(1)
121	725.63	97.99	End Shut-In(1)
122	103.60	98.01	Open To Flow (2)
152	127.83	99.07	Shut-In(2)
202	610.01	100.92	End Shut-In(2)
203	1649.68	101.14	Final Hydro-static

Recovery

Length (ft)	Description	Volume (bbl)
120.00	GO CUT M 30%GAS 35%O 30%M	1.68
180.00	GO 15%G 85%O	2.52

Gas Rates

Choke (inches)	Pressure (psia)	Gas Rate (Mcf/d)
----------------	-----------------	------------------

Superior Testers Enterprises LLC


Ref. No: 16694

Printed: 2009.03.16 @ 10:36:46

KANSAS CORPORATION COMMISSION

MAY 12 2009

RECEIVED



DRILL STEM TEST REPORT

MAI OIL OPERATIONS INC

MANETH #1

8411 PRESTON RD STE 800
DALLAS, TX 75225+5520

11-18S-15W BARTON

Job Ticket: 16695

DST#: 3

ATTN: KITT NOAH

Test Start: 2009.03.14 @ 12:50:00

GENERAL INFORMATION:

Formation: **LANSING KC H**

Deviated: No Whipstock ft (KB)

Time Tool Opened: 14:20:25

Time Test Ended: 18:44:55

Test Type: Conventional Bottom Hole (Initial)

Tester: JARED SCHECK

Unit No: 3320 - 35 - GB

Interval: **3433.00 ft (KB) To 3455.00 ft (KB) (TVD)**

Total Depth: 3455.00 ft (KB) (TVD)

Hole Diameter: 6.88 inches Hole Condition: Fair

Reference Elevations: 2001.00 ft (KB)

1993.00 ft (CF)

KB to GR/CF: 8.00 ft

Serial #: **27799** Inside

Press@RunDepth: 34.00 psia @ 3450.00 ft (KB)

Start Date: 2009.03.14 End Date: 2009.03.14

Start Time: 12:50:25 End Time: 18:44:55


Capacity: 5000.00 psia

Last Calib.: 2009.03.14

Time On Btm: 2009.03.14 @ 14:19:25

Time Off Btm: 2009.03.14 @ 17:21:55

TEST COMMENT: 45/INITIAL OPEN:VERY WEAK BUT BUILDING BLOW BUILT 1/2 INCH INTO BUCKET IN 45 MINUTES
45/INITIAL SHUT IN:VERY WEAK SURFACE BLOW
45/FINAL OPEN:VERY WEAK BT BUILDING BLOW BUILT 1/4 INCH INTO WATER IN 45 MINUTES
45/FINAL OPEN:NO BLOW BACK



PRESSURE SUMMARY


Time (Min.)	Pressure (psia)	Temp (deg F)	Annotation
0	1696.85	90.10	Initial Hydro-static
1	28.74	90.24	Open To Flow (1)
46	33.27	91.98	Shut-In(1)
91	37.42	94.53	End Shut-In(1)
91	33.15	94.56	Open To Flow (2)
134	34.00	96.78	Shut-In(2)
181	38.11	98.85	End Shut-In(2)
183	1688.85	98.97	Final Hydro-static

Recovery

Length (ft)	Description	Volume (bbl)
2.00	O CUT MUD 5%O 95%M	0.03

Gas Rates

Choke (inches)	Pressure (psia)	Gas Rate (Mcf/d)
----------------	-----------------	------------------



DRILL STEM TEST REPORT

MAI OIL OPERATIONS INC
8411 PRESTON RD STE 800
DALLAS, TX 75225+5520
ATTN: KITT NOAH


MANETH #1
11-18S-15W BARTON
Job Ticket: 16696 DST#: 4
Test Start: 2009.03.15 @ 02:05:00

GENERAL INFORMATION:

Formation: **LANSING KC I-J**
Deviated: No Whipstock: ft (KB)
Time Tool Opened: 04:04:55
Time Test Ended: 08:55:25
Interval: **3457.00 ft (KB) To 3492.00 ft (KB) (TVD)**
Total Depth: **3492.00 ft (KB) (TVD)**
Hole Diameter: **6.88 inches** Hole Condition: Fair
Test Type: Conventional Bottom Hole (Initial)
Tester: JARED SCHECK
Unit No: 3320- 35 - GB
Reference Elevations: 2001.00 ft (KB)
1993.00 ft (CF)
KB to GR/CF: 8.00 ft

Serial #: 27799 Inside
Press@RunDepth: 193.00 psia @ 3487.00 ft (KB)
Start Date: 2009.03.15 End Date: 2009.03.15
Start Time: 02:05:25 End Time: 08:55:25
Capacity: 5000.00 psia
Last Calib.: 2009.03.15
Time On Btm: 2009.03.15 @ 04:04:25
Time Off Btm: 2009.03.15 @ 07:13:25

TEST COMMENT: 45/INITIAL OPEN:STRONG BLOW BOTTOM OF BUCKET IN 2 MINUTES GAS TO SURFACE 27 MINUTES
45/INITIAL SHUT IN: 1 INCH BLOW BACK
45/FINAL OPEN:STRONG BLOW BUILT BOTTOM OF BUCKET IN 2 MINUTES
45/FINAL SHUT IN: BLOW BACK BOTTOM OF BUCKET IN 45 MINUTES



PRESSURE SUMMARY


Time (Min.)	Pressure (psia)	Temp (deg F)	Annotation
0	1729.66	88.81	Initial Hydro-static
1	81.49	88.93	Open To Flow (1)
46	125.36	95.16	Shut-In(1)
90	708.94	97.42	End Shut-In(1)
91	142.83	97.45	Open To Flow (2)
136	193.00	99.28	Shut-In(2)
189	665.21	101.11	End Shut-In(2)
189	1671.27	101.13	Final Hydro-static

Recovery

Length (ft)	Description	Volume (bbl)
120.00	GO CUT M 45%G 50%O 5%M	1.68
120.00	GO 5%G 90%O	1.68
180.00	OIL 100%	2.52
15.00	OIL 100%	0.21

Gas Rates

	Choke (inches)	Pressure (psia)	Gas Rate (Mcf/d)
First Gas Rate	0.25	5.30	8.41
Last Gas Rate	0.25	5.60	8.88
Max. Gas Rate	0.25	6.60	10.47



DRILL STEM TEST REPORT

MAI OIL OPERATIONS INC

MANETH #1

8411 PRESTON RD STE 800
DALLAS, TX 75225+5520

11-18S-15W BARTON

Job Ticket: 16697

DST#: 5

ATTN: KITT NOAH

Test Start: 2009.03.15 @ 21:45:00

GENERAL INFORMATION:

Formation: **ARBUCKLE**

Deviated: No Whipstock: ft (KB)

Time Tool Opened: 23:32:25

Time Test Ended: 04:04:54

Test Type: Conventional Bottom Hole (Initial)

Tester: JARED SCHECK

Unit No: 3320 - 35 - GB

Interval: **3566.00 ft (KB) To 3577.00 ft (KB) (TVD)**

Reference Elevations: 2001.00 ft (KB)

Total Depth: 3577.00 ft (KB) (TVD)

1993.00 ft (CF)

Hole Diameter: 6.88 inches Hole Condition: Fair

KB to GR/CF: 8.00 ft

Serial #: **27799**

Inside

Press@RunDepth: 229.80 psia @ 3572.00 ft (KB)

Capacity: 5000.00 psia

Start Date: 2009.03.15

End Date:

2009.03.16

Last Calib.:

2009.03.16

Start Time: 21:45:25

End Time:

04:04:55


Time On Btm:

2009.03.15 @ 23:31:25

Time Off Btm:

2009.03.16 @ 02:05:55

TEST COMMENT: 30/INITIAL OPEN:STRONG BLOW BOTTOM OF BUCKET IN 3 MINUTES
30/INITIAL SHUT-IN:3 INCH BLOW BACK
45/FINAL OPEN:FAIR BLOW BUILT BOTTOM OF BUCKET IN 10 MINUTES
45/FINAL SHUT-IN:4 1/2 INCH BLOW BACK



PRESSURE SUMMARY

Time (Min.)	Pressure (psia)	Temp (deg F)	Annotation
0	1791.92	96.62	Initial Hydro-static
1	117.66	97.00	Open To Flow (1)
31	146.98	110.29	Shut-In (1)
62	647.45	111.77	End Shut-In (1)
63	187.25	111.76	Open To Flow (2)
106	229.80	113.27	Shut-In (2)
154	747.74	113.65	End Shut-In (2)
155	1732.43	113.66	Final Hydro-static

Recovery

Length (ft)	Description	Volume (bbl)
60.00	GO CUT-M 10%G 80%O 10%M	0.84
495.00	GO 10%G 90%O	6.94
60.00	GAS ON TOP FLUID	0.84

Gas Rates

	Choke (inches)	Pressure (psia)	Gas Rate (Mcf/d)
--	----------------	-----------------	------------------