TRILOBITE TESTING, L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Drill-Stem Test Data

Well Name WHIPPLE "H" #1 Test No. 1 Date 2/10/93

Company PICKRELL DRILLING COMPANY, INC. Zone MARMATON

Address 110 N MARKET #205 WICHITA KS 67202 Elevation 2542

Co. Rep./Geo. BILL KLAVER Cont. PICKRELL DRLG RIG #10 Est. Ft. of Pay

Location: Sec. 6 Twp. 18S Rge. 26W Co. NESS State KS

Interval Tested 4274-4300

Anchor Length 26

Top Packer Depth 4269

Bottom Packer Depth 4274

Total Depth 4300

Drill Pipe Size 4.5 XH

Wt. Pipe I.D. - 2.7 Ft. Run

Drill Collar – 2.25 Ft. Run 177

Mud Wt. 9.5 lb/Gal.

Viscosity 47 Filtrate 9.6

Tool Open @ 2:13 AM Initial Blow 1/8" BLOW BUILDING TO 1/2" / THEN DECREASING TO SURFACE BLOW

Final Blow NO BLOW - FLUSHED TOOL - NO HELP

Recovery - Total Feet 2 Flush Tool? YES

Rec. 2 Feet of MUD

Rec. Feet of

Rec. Feet of

Rec. Feet of

Rec. Feet of

BHT 109 °F Gravity °API @ °F Corrected Gravity °API

RW @ °F Chlorides ppm Recovery Chlorides ppm System

(A) Initial Hydrostatic Mud 2213.6 PSI AK1 Recorder No. 22150 Range 3925

(B) First Initial Flow Pressure 32.4 PSI @ (depth) 4278 w / Clock No. 26199

(C) First Final Flow Pressure 40.5 PSI AK1 Recorder No. 24174 Range 3050

(D) Initial Shut-in Pressure 121.6 PSI @ (depth) 4297 w / Clock No. 27573

(E) Second Initial Flow Pressure 40.5 PSI AK1 Recorder No. Range

(F) Second Final Flow Pressure 40.5 PSI @ (depth) w / Clock No.

(G) Final Shut-in Pressure 51.6 PSI Initial Opening 30 Final Flow 30

(H) Final Hydrostatic Mud 2144.7 PSI Initial Shut-in 60 Final Shut-in 60

Our Representative PAUL SIMPSON

CHART PAGE



This is an actual photograph of recorder chart

	FIELD READING	OFFICE READING
(A) INITIAL HYDROSTATIC MUD	2206	2213.6
(B) FIRST INITIAL FLOW PRESSURE	30	32.4
(C) FIRST FINAL FLOW PRESSURE	37	40.5
(D) INITIAL CLOSED-IN PRESSURE	119	121.6
(E) SECOND INITIAL FLOW PRESSURE	37	40.5
(F) SECOND FINAL FLOW PRESSURE	37	40.5
(G) FINAL CLOSED-IN PRESSURE	44	51.6
(H) FINAL HYDROSTATIC MUD	2143	2144.7

TRILOBITE TESTING L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Test Ticket

№ 5845

Well Name & No. Whipple 'H' #1 Test No. 1 Date 2-10-93

Company Pickrell Drilling Co. Inc Zone Tested Marmaton

Address 110 N Market #205 Wichita Ks 67202 Elevation 2542 GL

Co. Rep./Geo. Bill Klaver Cont. P-D #10 Est. Ft. of Pay

Location: Sec. ~~36~~ 6 Twp. 18s Rge. 26w Co. Ness State Ks

No. of Copies 6 Distribution Sheet ____ Yes ____ No Turnkey ____ Yes ____ No ____ Evaluation

Interval Tested 4274-4300 Drill Pipe Size 4½ XH

Anchor Length 26 Top Choke — 1" ____ Bottom Choke — ¾" ____

Top Packer Depth 4269 Hole Size — 7⅞" ____ Rubber Size — 6¾" ____

Bottom Packer Depth 4274 Wt. Pipe I.D. — 2.7 Ft. Run ____

Total Depth 4300 Drill Collar — 2.25 Ft. Run 177

Mud Wt. 9.5 lb / gal. Viscosity 47 Filtrate 9.6

Tool Open @ 2:13 AM Initial Blow ⅛ blow building to ½ then decreasing to surface blow

Final Blow No blow - flushed tool - no help

Recovery — Total Feet 2 Feet of Gas in Pipe ____ Flush Tool? Y

Rec. 2	Feet Of Mud	%gas	%oil	%water	%mud
Rec. ____	Feet Of ____	%gas	%oil	%water	%mud
Rec. ____	Feet Of ____	%gas	%oil	%water	%mud
Rec. ____	Feet Of ____	%gas	%oil	%water	%mud
Rec. ____	Feet Of ____	%gas	%oil	%water	%mud

BHT 109 °F Gravity ____ °API @ ____ °F Corrected Gravity ____ °API

RW ____ @ ____ °F Chlorides ____ ppm Recovery Chlorides ____ ppm System

(A) Initial Hydrostatic Mud	2206 PSI	AK1 Recorder No.	22150	Range	3925
(B) First Initial Flow Pressure	30 PSI	@ (depth)	4278	w/Clock No.	26199
(C) First Final Flow Pressure	37 PSI	AK1 Recorder No.	24174	Range	3050
(D) Initial Shut-In Pressure	119 PSI	@ (depth)	4297	w/Clock No.	27533
(E) Second Initial Flow Pressure	37 PSI	AK1 Recorder No.	____	Range	____
(F) Second Final Flow Pressure	37 PSI	@ (depth)	____	w/Clock No.	____
(G) Final Shut-In Pressure	44 PSI	Initial Opening	30	Test	____
(H) Final Hydrostatic Mud	2143 PSI	Initial Shut-In	60	Jars	____
		Final Flow	30	Safety Joint	____
		Final Shut-In	60	Straddle	____
				Circ. Sub	____
				Sampler	____
				Extra Packer	____
				Other	____
				TOTAL PRICE $	____

Approved By Bill Klaver

Our Representative Paul Simpson

Printcraft Printers - Hays, KS

TRILOBITE TESTING, L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Drill-Stem Test Data

Well Name WHIPPLE "H" #1 Test No. 2 Date 2/11/93

Company PICKRELL DRILLING COMPANY, INC. Zone FORT SCOTT

Address 110 N MARKET #205 WICHITA KS 67202 Elevation 2542

Co. Rep./Geo. BILL KLAVER Cont. PICKRELL DRLG RIG #10 Est. Ft. of Pay

Location: Sec. 6 Twp. 18S Rge. 26W Co. NESS State KS

Interval Tested 4374-4415 Drill Pipe Size 4.5 XH

Anchor Length 41 Wt. Pipe I.D. - 2.7 Ft. Run

Top Packer Depth 4369 Drill Collar – 2.25 Ft. Run 149

Bottom Packer Depth 4374 Mud Wt. 9.3 lb/Gal.

Total Depth 4415 Viscosity 49 Filtrate 10.4

Tool Open @ 3:59 AM Initial Blow 1/4" BLOW DECREASING TO SURFACE

Final Blow NO BLOW - FLUSHED TOOL - NO HELP

Recovery - Total Feet 10 Flush Tool? YES

Rec. 10 Feet of MUD WITH OIL SPOTS IN TOOL

Rec. Feet of

Rec. Feet of

Rec. Feet of

Rec. Feet of

BHT 110 °F Gravity °API @ °F Corrected Gravity °API

RW @ °F Chlorides ppm Recovery Chlorides ppm System

(A) Initial Hydrostatic Mud 2243.7 PSI AK1 Recorder No. 22150 Range 3925

(B) First Initial Flow Pressure 32.4 PSI @ (depth) 4377 w / Clock No. 26199

(C) First Final Flow Pressure 40.5 PSI AK1 Recorder No. 24174 Range 3050

(D) Initial Shut-in Pressure 840.6 PSI @ (depth) 4412 w / Clock No. 27567

(E) Second Initial Flow Pressure 40.5 PSI AK1 Recorder No. Range

(F) Second Final Flow Pressure 40.5 PSI @ (depth) w / Clock No.

(G) Final Shut-in Pressure 663.5 PSI Initial Opening 30 Final Flow 30

(H) Final Hydrostatic Mud 2211.5 PSI Initial Shut-in 30 Final Shut-in 30

Our Representative PAUL SIMPSON

CHART PAGE



This is an actual photograph of recorder chart

	FIELD READING	OFFICE READING
(A) INITIAL HYDROSTATIC MUD	2240	2243.7
(B) FIRST INITIAL FLOW PRESSURE	30	32.4
(C) FIRST FINAL FLOW PRESSURE	37	40.5
(D) INITIAL CLOSED-IN PRESSURE	842	840.6
(E) SECOND INITIAL FLOW PRESSURE	37	40.5
(F) SECOND FINAL FLOW PRESSURE	37	40.5
(G) FINAL CLOSED-IN PRESSURE	660	663.5
(H) FINAL HYDROSTATIC MUD	2204	2211.5

TRILOBITE TESTING L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Test Ticket

№ 5846

Well Name & No. Whipple "H" #1 Test No. 2 Date 2-11-93

Company Pickrell Drilling Co, Inc Zone Tested Fort Scott

Address _____ Elevation 2542

Co. Rep./Geo. Bill Klaver Cont. Pickrell #10 Est. Ft. of Pay _____

Location: Sec. 6 Twp. 18s Rge. 26w Co. Ness State Ks

No. of Copies ~~5~~ Distribution Sheet _____ Yes _____ No Turnkey _____ Yes _____ No _____ Evaluation

Interval Tested 4374-4415 Drill Pipe Size 4½ XH

Anchor Length 41 Top Choke — 1" _____ Bottom Choke — ¾" _____

Top Packer Depth 4369 Hole Size — 7⅞" _____ Rubber Size — 6¾" _____

Bottom Packer Depth 4374 Wt. Pipe I.D. — 2.7 Ft. Run _____

Total Depth 4415 Drill Collar — 2.25 Ft. Run 149

Mud Wt. 9.3 lb / gal. Viscosity 49 Filtrate 10.4

Tool Open @ 3:59 AM Initial Blow ¼" blow decreasing to surface

Final Blow no blow - flush tool - no help

Recovery — Total Feet 10 Feet of Gas in Pipe _____ Flush Tool? Y

Rec. 10	Feet Of	Mud oil spots in tool	%gas	%oil	%water	%mud
Rec. _____	Feet Of		%gas	%oil	%water	%mud
Rec. _____	Feet Of		%gas	%oil	%water	%mud
Rec. _____	Feet Of		%gas	%oil	%water	%mud
Rec. _____	Feet Of		%gas	%oil	%water	%mud

BHT 110 °F Gravity _____ °API @ _____ °F Corrected Gravity _____ °API

RW _____ @ _____ °F Chlorides _____ ppm Recovery Chlorides _____ ppm System

(A) Initial Hydrostatic Mud	2240 PSI	AK1 Recorder No.	22150	Range	3925
(B) First Initial Flow Pressure	30 PSI	@ (depth)	4377	w/Clock No.	26199
(C) First Final Flow Pressure	37 PSI	AK1 Recorder No.	24174	Range	3050
(D) Initial Shut-In Pressure	842 PSI	@ (depth)	4412	w/Clock No.	27567
(E) Second Initial Flow Pressure	37 PSI	AK1 Recorder No.	_____	Range	_____
(F) Second Final Flow Pressure	37 PSI	@ (depth)	_____	w/Clock No.	_____
(G) Final Shut-In Pressure	660 PSI	Initial Opening	30	Test	_____
(H) Final Hydrostatic Mud	2204 PSI	Initial Shut-In	30	Jars	_____
		Final Flow	30	Safety Joint	_____
		Final Shut-In	30	Straddle	_____
				Circ. Sub	_____
				Sampler	_____
				Extra Packer	_____
				Other	_____
				TOTAL PRICE $	_____

Approved By Bill Klaver

Our Representative Paul Simpson

Printcraft Printers - Hays, KS

TRILOBITE TESTING, L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Drill-Stem Test Data

Well Name WHIPPLE "H" #1 Test No. 3 Date 2/11/93

Company PICKRELL DRILLING COMPANY, INC. Zone JOHNSON ZONE

Address 110 N MARKET #205 WICHITA KS 67202 Elevation 2542

Co. Rep./Geo. BILL KLAVER Cont. PICKRELL DRLG RIG #10 Est. Ft. of Pay

Location: Sec. 6 Twp. 18S Rge. 26W Co. NESS State KS

Interval Tested 4414-4465 Drill Pipe Size 4.5 XH

Anchor Length 51 Wt. Pipe I.D. - 2.7 Ft. Run

Top Packer Depth 4409 Drill Collar – 2.25 Ft. Run 149

Bottom Packer Depth 4414 Mud Wt. 9.3 lb/Gal.

Total Depth 4465 Viscosity 50 Filtrate 10.4

Tool Open @ 8:25 PM Initial Blow 1/2" BLOW DECREASED TO SURFACE BLOW

Final Blow NO BLOW - FLUSHED TOOL - NO HELP

Recovery - Total Feet 20 Flush Tool? YES

Rec. 20 Feet of MUD WITH OIL SPOTS IN TOOL

Rec. Feet of

Rec. Feet of

Rec. Feet of

Rec. Feet of

BHT 110 °F Gravity °API @ °F Corrected Gravity °API

RW @ °F Chlorides ppm Recovery Chlorides ppm System

(A) Initial Hydrostatic Mud 2250.8 PSI AK1 Recorder No. 22150 Range 3925

(B) First Initial Flow Pressure 40.5 PSI @ (depth) 4417 w / Clock No. 27567

(C) First Final Flow Pressure 51.6 PSI AK1 Recorder No. 24174 Range 3050

(D) Initial Shut-in Pressure 114.3 PSI @ (depth) 4462 w / Clock No. 26199

(E) Second Initial Flow Pressure 51.6 PSI AK1 Recorder No. Range

(F) Second Final Flow Pressure 51.6 PSI @ (depth) w / Clock No.

(G) Final Shut-in Pressure 70.4 PSI Initial Opening 30 Final Flow 30

(H) Final Hydrostatic Mud 2201.3 PSI Initial Shut-in 60 Final Shut-in 30

Our Representative PAUL SIMPSON

CHART PAGE



This is an actual photograph of recorder chart

	FIELD READING	OFFICE READING
(A) INITIAL HYDROSTATIC MUD	2251	2250.8
(B) FIRST INITIAL FLOW PRESSURE	37	40.5
(C) FIRST FINAL FLOW PRESSURE	44	51.6
(D) INITIAL CLOSED-IN PRESSURE	112	114.3
(E) SECOND INITIAL FLOW PRESSURE	44	51.6
(F) SECOND FINAL FLOW PRESSURE	44	51.6
(G) FINAL CLOSED-IN PRESSURE	67	70.4
(H) FINAL HYDROSTATIC MUD	2200	2201.3

TRILOBITE TESTING L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Test Ticket

№ 5847

Well Name & No. Whipple 'H' #1 Test No. 3 Date 2-11-93

Company Pickrell Drilling Co, Inc. Zone Tested Johnson Zone

Address _____ Elevation 2542

Co. Rep./Geo. Bill Klaver Cont. Pickrell #10 Est. Ft. of Pay _____

Location: Sec. 6 Twp. 18s Rge. 26w Co. Ness State Ks

No. of Copies _____ Distribution Sheet _____ Yes _____ No Turnkey _____ Yes _____ No _____ Evaluation

Interval Tested 4414-4465 Drill Pipe Size 4½ XH

Anchor Length 51 Top Choke — 1" _____ Bottom Choke — ¾" _____

Top Packer Depth 4409 Hole Size — 7⅞" _____ Rubber Size — 6¾" _____

Bottom Packer Depth 4414 Wt. Pipe I.D. — 2.7 Ft. Run _____

Total Depth 4465 Drill Collar — 2.25 Ft. Run 149

Mud Wt. 9.3 lb / gal. Viscosity 50 Filtrate 10.4

Tool Open @ 8:25 PM Initial Blow ½" blow decreased to surface blow

Final Blow no blow - flush tool - no blow

Recovery — Total Feet 20 Feet of Gas in Pipe _____ Flush Tool? Y

Rec. 20	Feet Of mud w/ oil spots	%gas	%oil	%water	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud

BHT 110 °F Gravity _____ °API @ _____ °F Corrected Gravity _____ °API

RW _____ @ _____ °F Chlorides _____ ppm Recovery Chlorides _____ ppm System

(A) Initial Hydrostatic Mud	2251 PSI	AK1 Recorder No.	22150	Range	3925
(B) First Initial Flow Pressure	37 PSI	@ (depth)	4417	w/Clock No.	27567
(C) First Final Flow Pressure	44 PSI	AK1 Recorder No.	24174	Range	3050
(D) Initial Shut-In Pressure	112 PSI	@ (depth)	4462	w/Clock No.	26199
(E) Second Initial Flow Pressure	44 PSI	AK1 Recorder No.	_____	Range	_____
(F) Second Final Flow Pressure	44 PSI	@ (depth)	_____	w/Clock No.	_____
(G) Final Shut-In Pressure	67 PSI	Initial Opening	30	Test	_____
(H) Final Hydrostatic Mud	2200 PSI	Initial Shut-In	60	Jars	_____
		Final Flow	30	Safety Joint	_____
		Final Shut-In	30	Straddle	_____
				Circ. Sub	_____
				Sampler	_____
				Extra Packer	_____
				Other	_____
				TOTAL PRICE $	_____

Approved By Bill Klaver

Our Representative Paul Simpson

Printcraft Printers - Hays, KS

TRILOBITE TESTING, L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Drill-Stem Test Data

Well Name WHIPPLE "H" #1 Test No. 4 Date 2/12/93

Company PICKRELL DRILLING COMPANY, INC. Zone MISS

Address 110 N MARKET #205 WICHITA KS 67202 Elevation 2542

Co. Rep./Geo. BILL KLAVER Cont. PICKRELL DRLG RIG #10 Est. Ft. of Pay 5

Location: Sec. 6 Twp. 18S Rge. 26W Co. NESS State KS

Interval Tested 4457-4494 Drill Pipe Size 4.5 XH

Anchor Length 37 Wt. Pipe I.D. - 2.7 Ft. Run

Top Packer Depth 4452 Drill Collar – 2.25 Ft. Run 179

Bottom Packer Depth 4457 Mud Wt. 9 lb/Gal.

Total Depth 4494 Viscosity 40 Filtrate 10.4

Tool Open @ 1:49 PM Initial Blow 3/4" BLOW BUILDING TO 3"

Final Blow WEAK SURFACE BLOW BUILDING TO 4"
NO BLOW BACK ON SHUT IN

Recovery - Total Feet 195 Flush Tool? NO

Rec. 140 Feet of GAS IN PIPE

Rec. 15 Feet of CLEAN GASSY OIL-10%GAS/90%OIL

Rec. 120 Feet of HVY OIL CUT MUD-40%OIL/60%MUD

Rec. 60 Feet of OIL CUT MUD-15% OIL/85%MUD

Rec. Feet of

BHT 119 °F Gravity °API @ °F Corrected Gravity °API

RW @ °F Chlorides ppm Recovery Chlorides ppm System

(A) Initial Hydrostatic Mud 2213.6 PSI AK1 Recorder No. 22150 Range 3925

(B) First Initial Flow Pressure 50.3 PSI @ (depth) 4460 w / Clock No. 26194

(C) First Final Flow Pressure 70.4 PSI AK1 Recorder No. 24174 Range 3050

(D) Initial Shut-in Pressure 1105.6 PSI @ (depth) 4490 w / Clock No. 27567

(E) Second Initial Flow Pressure 78.9 PSI AK1 Recorder No. Range

(F) Second Final Flow Pressure 110.3 PSI @ (depth) w / Clock No.

(G) Final Shut-in Pressure 967.5 PSI Initial Opening 30 Final Flow 120

(H) Final Hydrostatic Mud 2115.4 PSI Initial Shut-in 60 Final Shut-in 90

Our Representative PAUL SIMPSON

CHART PAGE



This is an actual photograph of recorder chart

	FIELD READING	OFFICE READING
(A) INITIAL HYDROSTATIC MUD	2206	2213.6
(B) FIRST INITIAL FLOW PRESSURE	52	50.3
(C) FIRST FINAL FLOW PRESSURE	67	70.4
(D) INITIAL CLOSED-IN PRESSURE	1100	1105.6
(E) SECOND INITIAL FLOW PRESSURE	74	78.9
(F) SECOND FINAL FLOW PRESSURE	104	110.3
(G) FINAL CLOSED-IN PRESSURE	963	967.5
(H) FINAL HYDROSTATIC MUD	2112	2115.4

CALCULATED RECOVERY ANALYSIS

DST # 4 TICKET # 5848

SAMPLE #	TOTAL FEET	GAS %	GAS FEET	OIL %	OIL FEET	WATER %	WATER FEET	MUD %	MUD FEET
DRILL 1	15	10	1.5	90	13.5	0	0	0	0
PIPE 2	1	0	0	40	0.4	0	0	60	0.6
3			0		0		0		0
4			0		0		0		0
5			0		0		0		0
6			0		0		0		0
WEIGHT 1			0		0		0		0
PIPE 2			0		0		0		0
3			0		0		0		0
4			0		0		0		0
DRILL 1	119	0	0	40	47.6	0	0	60	71.4
COLLAR 2	60	0	0	15	9	0	0	85	51
3			0		0		0		0
4			0		0		0		0
5			0		0		0		0
TOTAL	195		1.5		70.5		0		123

			HRS OPEN	BBL/DAY
BBL OIL=	0.474432	*	2.5	4.5545472
BBL WATER=	0	*		0
BBL MUD=	0.607068			
BBL GAS =	0.02133			



TRILOBITE TESTING L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Test Ticket

№ 5848

Well Name & No. Whipple 'H' #1 Test No. 4 Date 2-12-93

Company Pickrell Drilling Co, Inc Zone Tested Miss

Address _____ Elevation 2542

Co. Rep./Geo. Bill Klaver Cont. Pickrell #10 Est. Ft. of Pay 5

Location: Sec. 6 Twp. 18s Rge. 26w Co. Ness State Ks

No. of Copies _____ Distribution Sheet _____ Yes _____ No Turnkey _____ Yes _____ No _____ Evaluation

Interval Tested 4457-4494 Drill Pipe Size 4½ XH

Anchor Length 37 Top Choke — 1" _____ Bottom Choke — ¾" _____

Top Packer Depth 4452 Hole Size — 7⅞" _____ Rubber Size — 6¾" _____

Bottom Packer Depth 4457 Wt. Pipe I.D. — 2.7 Ft. Run _____

Total Depth 4494 Drill Collar — 2.25 Ft. Run 179

Mud Wt. 9.0 lb / gal. Viscosity 40 Filtrate 10.4

Tool Open @ 1:49 PM Initial Blow 3/4" blow building to 3½"

Final Blow weak surface blow building to 4"
No blow back on shutin

Recovery — Total Feet 195 Feet of Gas in Pipe 140 Flush Tool? _____

Rec.	15	Feet Of	cl gassyoil		10 %gas	90 %oil	%water		%mud
Rec.	120	Feet Of	HOCM		%gas	40 %oil	%water	60	%mud
Rec.	60	Feet Of	OCM		%gas	15 %oil	%water	85	%mud
Rec.		Feet Of			%gas	%oil	%water		%mud
Rec.		Feet Of			%gas	%oil	%water		%mud

BHT 119 °F Gravity _____ °API @ _____ °F Corrected Gravity _____ °API

RW _____ @ _____ °F Chlorides _____ ppm Recovery Chlorides _____ ppm System

(A) Initial Hydrostatic Mud	2206 PSI	AK1 Recorder No.	22150	Range	3925
(B) First Initial Flow Pressure	52 PSI	@ (depth)	4460	w/Clock No.	26199
(C) First Final Flow Pressure	67 PSI	AK1 Recorder No.	24174	Range	3050
(D) Initial Shut-In Pressure	1100 PSI	@ (depth)	4490	w/Clock No.	27567
(E) Second Initial Flow Pressure	74 PSI	AK1 Recorder No.		Range	
(F) Second Final Flow Pressure	104 PSI	@ (depth)		w/Clock No.	
(G) Final Shut-In Pressure	963 PSI	Initial Opening	30	Test	
(H) Final Hydrostatic Mud	2112 PSI	Initial Shut-In	60	Jars	
		Final Flow	120	Safety Joint	
		Final Shut-In	90	Straddle	
				Circ. Sub	
				Sampler	
				Extra Packer	
				Other	
				TOTAL PRICE $	

Approved By Bill Klaver

Our Representative Paul Simpson

Printcraft Printers - Hays, KS

TRILOBITE TESTING, L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Drill-Stem Test Data

Well Name WHIPPLE "H" #1 Test No. 5 Date 2/13/93

Company PICKRELL DRILLING COMPANY, INC. Zone MISS

Address 110 N MARKET #205 WICHITA KS 67202 Elevation 2542

Co. Rep./Geo. BILL KLAVER Cont. PICKRELL DRLG RIG #10 Est. Ft. of Pay

Location: Sec. 6 Twp. 18S Rge. 26W Co. NESS State KS

Interval Tested 4494-4502 Drill Pipe Size 4.5 XH

Anchor Length 8 Wt. Pipe I.D. - 2.7 Ft. Run

Top Packer Depth 4489 Drill Collar – 2.25 Ft. Run 179

Bottom Packer Depth 4494 Mud Wt. 9 lb/Gal.

Total Depth 4502 Viscosity 46 Filtrate 11.2

Tool Open @ 7:51 AM Initial Blow 3/4" BLOW BUILDING TO 1.5"

Final Blow NO BLOW - FLUSHED TOOL - NO BLOW

Recovery - Total Feet 65 Flush Tool? YES

Rec. 2 Feet of CLEAN OIL

Rec. 63 Feet of SLTLY OIL CUT THIN MUD - 5%OIL/95%MUD

Rec. Feet of

Rec. Feet of

Rec. Feet of

BHT 111 °F Gravity °API @ °F Corrected Gravity °API

RW 0.88 @ 40 °F Chlorides 13000 ppm Recovery Chlorides 3000 ppm System

(A) Initial Hydrostatic Mud 2306.9 PSI AK1 Recorder No. 22150 Range 3925

(B) First Initial Flow Pressure 32.4 PSI @ (depth) 4496 w / Clock No. 26199

(C) First Final Flow Pressure 40.5 PSI AK1 Recorder No. 24174 Range 3050

(D) Initial Shut-in Pressure 1240.6 PSI @ (depth) 4500 w / Clock No. 27573

(E) Second Initial Flow Pressure 51.6 PSI AK1 Recorder No. Range

(F) Second Final Flow Pressure 51.6 PSI @ (depth) w / Clock No.

(G) Final Shut-in Pressure 1226.9 PSI Initial Opening 30 Final Flow 30

(H) Final Hydrostatic Mud 2144.7 PSI Initial Shut-in 60 Final Shut-in 60

Our Representative PAUL SIMPSON

CHART PAGE



This is an actual photograph of recorder chart

	FIELD READING	OFFICE READING
(A) INITIAL HYDROSTATIC MUD	2294	2306.9
(B) FIRST INITIAL FLOW PRESSURE	30	32.4
(C) FIRST FINAL FLOW PRESSURE	37	40.5
(D) INITIAL CLOSED-IN PRESSURE	1243	1240.6
(E) SECOND INITIAL FLOW PRESSURE	44	51.6
(F) SECOND FINAL FLOW PRESSURE	44	51.6
(G) FINAL CLOSED-IN PRESSURE	1220	1226.9
(H) FINAL HYDROSTATIC MUD	2151	2144.7

TRILOBITE TESTING L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Test Ticket

№ 5849

Well Name & No. Whippk 'H' #1 Test No. 5 Date 2-13-93

Company Pickrell Drilling Co, Inc Zone Tested Miss

Address _____ Elevation _____

Co. Rep./Geo. Bill Klaver Cont. Pickrell #10 Est. Ft. of Pay _____

Location: Sec. 6 Twp. 18s Rge. 26w Co. Ness State Ks

No. of Copies _____ Distribution Sheet _____ Yes _____ No Turnkey _____ Yes _____ No _____ Evaluation

Interval Tested 4494 - 4502 Drill Pipe Size 4½ XH

Anchor Length 8 Top Choke — 1" _____ Bottom Choke — ¾" _____

Top Packer Depth 4489 Hole Size — 7⅞" _____ Rubber Size — 6¾" _____

Bottom Packer Depth 4494 Wt. Pipe I.D. — 2.7 Ft. Run _____

Total Depth 4502 Drill Collar — 2.25 Ft. Run 179

Mud Wt. 9.0 lb / gal. Viscosity 46 Filtrate 11.2

Tool Open @ 7:51 AM Initial Blow ¾" blow building to 1½

Final Blow no blow - flush tool - no blow

Recovery — Total Feet 65 Feet of Gas in Pipe _____ Flush Tool? _____

Rec. 2	Feet Of cl oil	%gas	%oil	%water	%mud
Rec. 63	Feet Of soc thin mud	%gas 5	%oil	%water 95	%mud
Rec. _____	Feet Of	%gas	%oil	%water	%mud
Rec. _____	Feet Of	%gas	%oil	%water	%mud
Rec. _____	Feet Of	%gas	%oil	%water	%mud

BHT 111 °F Gravity _____ °API @ _____ °F Corrected Gravity _____ °API

RW .88 @ 40 °F Chlorides 13,000 ppm Recovery Chlorides 3,000 ppm System

(A) Initial Hydrostatic Mud	2294 PSI	AK1 Recorder No. 22150	Range 3925
(B) First Initial Flow Pressure	30 PSI	@ (depth) 4496	w/Clock No. 26199
(C) First Final Flow Pressure	37 PSI	AK1 Recorder No. 24174	Range 3050
(D) Initial Shut-In Pressure	1243 PSI	@ (depth) 4500	w/Clock No. 27523
(E) Second Initial Flow Pressure	44 PSI	AK1 Recorder No. _____	Range _____
(F) Second Final Flow Pressure	44 PSI	@ (depth) _____	w/Clock No. _____
(G) Final Shut-In Pressure	1220 PSI	Initial Opening 30	Test _____
(H) Final Hydrostatic Mud	2151 PSI	Initial Shut-In 60	Jars _____
		Final Flow 30	Safety Joint _____
		Final Shut-In 60	Straddle _____
			Circ. Sub _____
			Sampler _____
			Extra Packer _____
			Other _____
			TOTAL PRICE $ _____

Approved By Klaver, Bill

Our Representative Paul Simpson

Printcraft Printers - Hays, KS

TRILOBITE TESTING, L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Drill-Stem Test Data

Well Name WHIPPLE "H" #1 Test No. 6 Date 2/13/93

Company PICKRELL DRILLING COMPANY, INC. Zone MISS

Address 110 N MARKET #205 WICHITA KS 67202 Elevation 2542

Co. Rep./Geo. BILL KLAVER Cont. PICKRELL DRLG RIG #10 Est. Ft. of Pay

Location: Sec. 6 Twp. 18S Rge. 26W Co. NESS State KS

Interval Tested 4498-4506 Drill Pipe Size 4.5 XH

Anchor Length 8 Wt. Pipe I.D. - 2.7 Ft. Run

Top Packer Depth 4493 Drill Collar – 2.25 Ft. Run 179

Bottom Packer Depth 4498 Mud Wt. 9 lb/Gal.

Total Depth 4506 Viscosity 46 Filtrate 11.2

Tool Open @ 10:12 PM Initial Blow (SLID TOOL 1 FT WHEN OPENED) - 1/2" BLOW BUILDING TO 1.25"

Final Blow NO BLOW - NO BLOW AFTER SURGE

Recovery - Total Feet 70 Flush Tool? YES

Rec. 70 Feet of MUDDY WATER

Rec. Feet of

Rec. Feet of

Rec. Feet of

Rec. Feet of

BHT 113 °F Gravity °API @ °F Corrected Gravity °API

RW 0.98 @ 50 °F Chlorides 9000 ppm Recovery Chlorides 3000 ppm System

(A) Initial Hydrostatic Mud 2306.9 PSI AK1 Recorder No. 22150 Range 3925

(B) First Initial Flow Pressure 32.4 PSI @ (depth) 4500 w / Clock No. 26199

(C) First Final Flow Pressure 40.5 PSI AK1 Recorder No. 24174 Range 3050

(D) Initial Shut-in Pressure 1250.6 PSI @ (depth) 4504 w / Clock No. 19960

(E) Second Initial Flow Pressure 51.6 PSI AK1 Recorder No. Range

(F) Second Final Flow Pressure 51.6 PSI @ (depth) w / Clock No.

(G) Final Shut-in Pressure 1255.6 PSI Initial Opening 30 Final Flow 30

(H) Final Hydrostatic Mud 2170.6 PSI Initial Shut-in 60 Final Shut-in 60

Our Representative PAUL SIMPSON

CHART PAGE



This is an actual photograph of recorder chart

	FIELD READING	OFFICE READING
(A) INITIAL HYDROSTATIC MUD	2299	2306.9
(B) FIRST INITIAL FLOW PRESSURE	30	32.4
(C) FIRST FINAL FLOW PRESSURE	37	40.5
(D) INITIAL CLOSED-IN PRESSURE	1258	1250.6
(E) SECOND INITIAL FLOW PRESSURE	44	51.6
(F) SECOND FINAL FLOW PRESSURE	44	51.6
(G) FINAL CLOSED-IN PRESSURE	1251	1255.6
(H) FINAL HYDROSTATIC MUD	2174	2170.6

TRILOBITE TESTING L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Test Ticket

№ 5850

Well Name & No. Whipple "H" #1 Test No. 6 Date 2-13-93

Company Pickrell Drilling Co. Inc Zone Tested Miss

Address _____ Elevation _____

Co. Rep./Geo. Bill Klaver Cont. _____ Est. Ft. of Pay _____

Location: Sec. 6 Twp. 18s Rge. 26w Co. Ness State Ks

No. of Copies _____ Distribution Sheet _____ Yes _____ No Turnkey _____ Yes _____ No _____ Evaluation

Interval Tested 4498-4506 Drill Pipe Size 4½ XH

Anchor Length 8 Top Choke — 1" _____ Bottom Choke — ¾" _____

Top Packer Depth 4493 Hole Size — 7⅞" _____ Rubber Size — 6¾" _____

Bottom Packer Depth 4498 Wt. Pipe I.D. — 2.7 Ft. Run _____

Total Depth 4506 Drill Collar — 2.25 Ft. Run 179

Mud Wt. 9.0 lb / gal. Viscosity 46 Filtrate 11.2

Tool Open @ 10:12 PM Initial Blow (slid tool 1' when opened) - ½" blow building to 1¼"

Final Blow no blow - no blow after surge

Recovery — Total Feet 70 Feet of Gas in Pipe _____ Flush Tool? Y

Rec. 70	Feet Of Muddy water	%gas	%oil 10	%water 90	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud
Rec. _____	Feet Of _____	%gas	%oil	%water	%mud

BHT 113 °F Gravity _____ °API @ _____ °F Corrected Gravity _____ °API

RW .98 @ 50 °F Chlorides 9,000 ppm Recovery Chlorides 3000 ppm System

(A) Initial Hydrostatic Mud	2299 PSI	AK1 Recorder No.	22150	Range	3925
(B) First Initial Flow Pressure	30 PSI	@ (depth)	4500	w/Clock No.	26179
(C) First Final Flow Pressure	37 PSI	AK1 Recorder No.	24174	Range	3050
(D) Initial Shut-In Pressure	1258 PSI	@ (depth)	4504	w/Clock No.	19960
(E) Second Initial Flow Pressure	44 PSI	AK1 Recorder No.	_____	Range	_____
(F) Second Final Flow Pressure	44 PSI	@ (depth)	_____	w/Clock No.	_____
(G) Final Shut-In Pressure	1251 PSI	Initial Opening	30	Test	_____
(H) Final Hydrostatic Mud	2174 PSI	Initial Shut-In	60	Jars	_____
		Final Flow	30	Safety Joint	_____
		Final Shut-In	60	Straddle	_____
				Circ. Sub	_____
				Sampler	_____
				Extra Packer	_____
				Other	_____
				TOTAL PRICE $	_____

Approved By Bill Klaver

Our Representative Paul Simpson

Printcraft Printers - Hays, KS