
WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bank Bldg. Wichita, Kansas.

CITIES SERVICE OIL CO.
Zajic No. 3

SEC. 11 T. 18 R. 8W.
NE SE
330' S 330' W E1/4 cor.

Total Depth. 3288
Comm. 6-16-39 Comp. 7-11-39
Shot or treated.
Contractor H.B.Mabee
Issued. 8-19-39

County Rice.



CASING. Rotary 3255
Cable 3288

10 3/4" 250'
5 1/2" 3250'

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

surface clay	40
shale	130
shale and shells	250
shale and red bed	310
lime	335
shale and shells	805
salt and shale	920
shale and shells	950
lime	1090
shale and lime shells	1170
lime broken	1270
broken lime	1350
lime and shale	1482
lime broken	1568
lime and shale	1736
lime	1741
shale and shells	1815
shale and lime	2052
shale and shells	2203
shale	2297
lime broken	2343
shale	2393
shale and lime	2446
lime broken	2498
shale and lime	2617
lime broken	2827
shale	2846
lime	2888
lime broken	2927
lime	3136
broken lime	3188
lime	3229
lime and shale	3240
shale	3252

Top Arbuckle 3251
core 3252-58 5 1/2' rec. dolomite
lime 3258
T.D. rotary 3258 equals 3255 S.L.M.
lime 3288
Total Depth.

Top Arbuckle 3248 Corr.
Penetration 40
Total Depth 3288

Top K.C. 2832

2846-52 fair porosity & stain to sat.
2980-09 poor to fair
2927-58 fair to good por. no sat.
3127-33 crystalline, poor porosity
good sat.

1 bailer water 3286-88
Rotary tools 3255
cable tools 3288