WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
412 Union National Bk Bldg., Wichita, Kansas.

SKELLY OIL COMPANY
D.F.Dittmers No. 2.

SEC. 28 T. 19 R. 10W
SWc SW
330' fr SL 330' fr WL

Total Depth. 3275'
Comm. 2-25-37 Comp. 3-22-37
Shot or Treated. 2000 & 2500
Contractor. Olson Drlg.Co.
Issued. 4-24-37

Rotary 0-3269
Cable 3269-75

CASING:
13" 186'
7" 3264'

County. Rice



Elevation. 1779

Production. Pot. 2334 B. after shot.
Est. 5,000 Gas.

Figures Indicate Bottom of Formations.

surface soil, sand & clay	50
shale & sdy clay	110
shale blue	160
hrd sharp sand	175
shale	186
red beds	253
shale red	505
shale & lime	850
shale & shells	1095
salt & shale	1225
brkn lime	1492
lime	1550
shale & shells	1578
lime & brkn lime	1706
brkn lime	1740
lime	2075
brkn lime	2117
shale & shells	2280
brkn lime	2325
lime	2610
sticky shale & lime hrd	2651
lime	2840
lime with streaks shale	2861
brkn lime	2885
sticky shale	2907
brkn lime & shale	2949
sticky shale	2970
shale, red rock & shells	2995
lime	3058
brkn lime	3075
brkn lime & lime	3113
lime & brkn lime	3146
lime	3203
shale, shells & sticky shale	3235
shale	3250
lime	3265

cored 3265-70
Steel line corr. 3270-3269
Top Siliceous lime 3264
Standardized rig at 3269

brown porous dolomite	3270
Oil saturation.	
dense brown cherty lime	3272
med. brown hrd dolomite	3275
Slight saturation & porosity	

Total Depth.

3264 9/3
3272
1
1A
1

Prod. before acid 2000' oil in hole in 9 hrs.
Prod. after acid 2334 B.(Pumped in 24-hr test.)

2000 Gals. 3264-3270 2500 Gals. 3264-75

Siliceous lime Top 3264
Main body pay formation 3264-3275