

STANOLIND OIL AND GAS CO.
 L. F. Manke No. 1.


SEC. 28 T. 19 R. 10W.
 SW SW SE
 330' N of S.L.
 330' E of W.L.

Total Depth. 3272 P.B. 3261'
 Comm. 6-16-37 Comp. 8-2-37
 Shot or Treated. 1000 gal. 200 gal.
 Contractor.
 Issued. 10-9-37

County. Rice.

CASING.

10 3/4" 202'
 6" 3257'



Elevation. 1778

Production. DRY.

Figures Indicate Bottom of Formations.

| | |
|------------------------|----------------|
| sand | 40 |
| surface soil and sand | 120 |
| shale and shells | 2 02 |
| shale and red rock | 388 |
| red rock | 440 |
| anhydrite | 465 |
| shale and shells | 1065 |
| salt | 1200 |
| shale and shells | 1300 |
| broken lime | 1410 |
| shale and shells | 1465 |
| broken lime | 1955 |
| shale and shells | 2325 |
| lime | 2355 |
| broken lime | 2590 |
| lime | 2780 |
| broken lime | 2785 |
| lime | 2850 |
| shale | 2900 |
| broken lime | 2965 |
| shale and shells | 2980 |
| lime | 3060 |
| lime soft | 3090 |
| lime | 3270 |
| (3263-3270 soft) | |
| dolomite slight Porous | 3272 with S.O. |
| Total Depth. | |

Handwritten calculation:
 3257
 1778

 1479

CORING RECORD.

Note- Top of Siliceous 3257 ft by
 samples top of Siliceous was not
 anticipated so high hense was drilled.

Core No. 1.

Dolomite slightly porous with
 O.S. 3270-3272

Sample analysis from Top of Siliceous.

lime white trace of dolomite 3257-3259
 dolomite white mod cryst. 3259-3261 1/2
 dolomite wh. mod cryst. porous
 with good O.S. 3261 1/2-3270

Plugged back 3272 to 3265 1/2"

cemented back 3270-3261

siliceous lime 3257-3272