


VICKERS PETRO.CO., INC.
Herr "C" No. 2.

SEC.24 T.19 R.11 W
CNL SE SE

Total Depth. 3341'
Comm. 1-7-43 Comp. 2-11-43
Shot or Treated.
Contractor.
Issued. 3-20-43

County. Barton



CASING:

10 $\frac{3}{4}$ " 180' Cem.
5 $\frac{1}{2}$ " 3319' Cem.

Elevation.

Production. Pot. 387 Oil
40% wtr

Figures Indicate Bottom of Formations.

surface	0-185
red bed	480
anhydrite	500
red bed & shale	990
salt & shale	1305
anhydrite	1345
shale & shells	1430
lime & shale	1650
sand	1685
lime & shale	1760
lime brkn	1865
lime & shale	1965
shale & lime	2090
shale & shells	2380
lime brkn	2420
lime & shale	2665
lime	2900
lime & shale	3027
lime	3325
SLC 3320 equals	3324
lime	3321-3338
350' OIH 14 hrs	
600' OIH 22 hrs, no wtr	
2000 Acid (took 600 gal. @1300#/sq.in. no help)	
lime ?	3341
1000 Acid	
1200' OIH 1 hr	
2770' OIH 15 hrs, sh wtr	
Potential 387 oil; 40% wtr	
Total Depth	3341

Tops:

Lansing K.C.

Brown Lime 2999

White Lime 3015

Arbuckle dolomite 3318