Company. SINCLAIR OIL & GAS COMPANY
Farm. Lillie Evers No. 1
AE#140

SEC. 24 T. 19 R. 11W
SE SE SW
330' fm South & West lines,
S/2 SW¼
County Barton
KANSAS

Total Depth. 3496 PB 3476
Comm. 2-13-52 Comp. 2-26-52
Shot or Treated.
Contractor. Adkins Drilling Co.
Issued. 5-31-52

Elevation. 1869 Rig Floor

Production. 25 bbls, Temporary

CASING:
10 3/4" 780' cem w/375 sx
7" 3496' cem w/250 sx
2" Tubing 3236' 12' subs tbg is 10' off bottom.

Figures Indicate Bottom of Formations.

sand	96	Drillers Log Surface Level Measurements.
sand, shale	271	Zero - 5'4" top of Rot. Bushing to Top 7" Spider.
sand	406	
sand, shale, red bed	446	Ran Schlumberger 2/27/1952
red bed, shale	772	T.D. 3496' in Arbuckle
anhydrite	781	
shale, redbed, shells	1506	
shale, lime	1806	
drlg 9" hole		
lime, shale	2101	
shale, lime, shells	2401	
lime, shale	2556	
shale, lime shells	2685	
lime, shale	2851	
lime	2933	
lime, chert	2991	
lime, shale	3046	
lime	3091	
lime, shale	3241	
lime	3422	
conglomerate	3490	
lime	3496	
Total Depth		
Plugged back 3476		

Tops:

Anhydrite	773	
Heebner (Scout)	3084	
Lansing (Sample)	3186	Ground Level Meas.
Brown Lime (Scout)	3190	(Add 4' for RBM)
Conglomerate (Sample)	3422	
Arbuckle (Sample)	3490	

P.D.-T.D. 3472
3/5/52 Perf. Lan-K.C.
24 shots 3336-40
No show oil, gas or water.
" 1000 Gals. acid, on Vacuum, 140 bbl wtr load (Dowell)
After acid load recovered, swabbed 4 BWPH for e hrs.
No oil or Gas.
Set bridging plug @ 3276' PB-TD
3/6/52 Perf. Lan-KC 23 holes 3251-55
Est. 100,000 cu ft gas, oil fillup 200' in 24 mins.
3/6/52 Recovered 15 bbls oil after 3 runs of swab. Let stand 1 hr & rec. 6 bbls oil on one run.
3/6/52 Dowell 1000 gals acid on vacuum, 131 bbls water load, after acid load rec. swabbed 257 bbls oil no water, in 9 hrs.
Last 3 hrs averaged 15 bbls oil an hr.