15-039-00530

11-1-27W

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company CITIES SERVICE OIL CO.
Farm Warner "E" No. 3

SEC. 11 T. 1 R. 27W
SW NW SE
990' S 330' N of Cen.

Total Depth 3420' PB 3360'
Comm. 7-9-57 Comp. 7-18-57
Shot or Treated.
Contractor Lohmann-Johnson Drlg. Co., Inc.
Issued 9-28-57

County Decatur
KANSAS

Elevation 2514'

CASING:
8 5/8" 320' w/250 sx cem.
5½" 3417' w/200 sx cem.
DV tool 1873' w/400 sx cem.

Production. Phy.Pot. 204 B.O., 8% wtr. PD

Figures Indicate Bottom of Formations.

sand-shale	320
shale	1390
shale-lime	1660
lime	1870
anhydrite	1900
shale-lime	2400
lime	2600
lime-shale	2675
lime	3420

3420 Rotary T.D. = 3418 SLM
Total Depth PB 3360

Corr.	Howead	2912
	Severy (Scout)	2998
"	Topeka	3022
"	Lansing	3182
"	B/Kansas City	3398
"	Penn. sand	3401

Drilled cement to 3412 S.L.M.

Perf. 36 shots 3400-07
7-25-57 - Petrofrac w/4000# sand and 4000 gals. Petrogel; used 301 BO; did not recover all of load oil.

41 shots 3300-3310
24 " 3224-30
17 " 3214-18
49 " 3190-92

Acidizing Record 7-31-57:
1250 gals. 3300-3310
750 " 3224-30
500 " 3214-18
1000 " 3180-92