

KANSAS GEOLOGICAL SOCIETY
 KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
 KANSAS GEOLOGICAL SOCIETY BUILDING
 508 EAST MURDOCK - WICHITA, KANSAS

20-1-32W

COMPANY SKELLY OIL

SEC. 20 T. 1 R. 32W

FARM E. H. Wicke

NO. 5

LOC. C N $\frac{1}{2}$ NE SE

TOTAL DEPTH 4210'

COMM. 3-3-67

COMP. 3-9-67


SHOT OR TREATED

CONTRACTOR Murfin Drlg.

ISSUED 5-27-67

COUNTY Rawlins

KANSAS



CASING

20	10	
15	8	5/8" 367' cem w/ 275 sx
12	6	
13	5	1/2" 4210' cem w/ 250 sx

ELEVATION 3006' KB

PRODUCTION 79 BOPD PLUS 1%
 WTR, GR 34.8, Lans ~~3996~~ 4006
 4016-36

FIGURES INDICATE BOTTOM OF FORMATIONS

- 40 Surface Clay
- 250 Shale-Sand
- 320 Sand & Shale
- 370 Shale
- 370 Cement
- 950 Shale
- 1690 Shale & Sand
- 2115 Sand - Shale
- 2455 Shale-Lime
- 2630 Lime & Shale
- 2771 Shale & Red Bed
- 2805 Anhydrite
- 3156 Shale-Lime
- 3760 Lime & Shale
- 4210 Lime

TOPS: SCOUT

Lansing	3916
Lansing G	3995
Lansing J	4096
Lansing K	4142

State of KANSAS

County of SEDGWICK

55: