



1-1-34W
15-153-20,215
Well No. 2

Lease Name: Fikan AB
 Well Located: C NE SW
Rawlins SEC I TWP IS RGE 34W
 Operator: PICKRELL DRILLING COMPANY
 Address: Litwin Bldg. Suite 205-110 N. Market Wichita, Ks. 67202
 Elevation: Ground 3005 D.F. 3007 K.B. 3010
 Type Well: (Oil, gas, dry hole) OTT

Drilling Commenced: 7-6-75 1975 Drilling Completed: 8-5- 1975
 Well Completed: 8-19 1975 Total Depth 4220
 Initial Production: _____

Casing Record

Size: 8 5/8 Set at 208 Size: _____ Set at _____
 Size: 5 1/2 Set at 4216 Size: _____ Set at _____

Liner Record

Size: _____ Set from _____ To _____

Cementing

<u>Casing Size</u>	<u>Sacks</u>	<u>Type Cement and Additives</u>
<u>8 5/8</u>	<u>150</u>	_____
<u>5 1/2</u>	<u>125</u>	_____
_____	_____	_____

Perforations

<u>Formation</u>	<u>Perforated Interval and Number Shots</u>
_____	<u>4166-67 2/DP</u>
_____	<u>4157-58 1/DP</u>
_____	<u>4097-4102 2/DP</u>
_____	<u>3981-83 2/DP</u>



Electric Log Run . (Show type log and depths covered)

Petro-Log. Gamma Ray Neutron

(Fill in formation and related information on reverse side)

1-1-34w
p. 2

Show Drill Stem Tests,
Well Stimulation and
Production Tests

Formation Top Bottom

Top Soil	0	208
Shale	208	290
Shale	290	1365
Shale	1365	2190
Shale	2190	2320
Sand	2320	2410
Hard Sand	2410	2445
Shale	2445	2540
Sandy Lime	2540	2570
Shale & Lime	2570	2856
Shale	2856	2886
Shale	2886	3100
S	3100	3130
Lime & Shale	3130	3315
Lime & Shale	3315	3473
Lime & Shale	3473	3590
Shale & Lime	3590	3710
L	3710	3775
Lime	3775	3857
Lime & Shale	3857	3918
Sand	3918	3935
Lime	3935	3940
Lime	3940	3965
Lime	3965	3990
Lime	3990	4025
Lime	4025	4040
Lime & Shale	4040	4065
Lime	4065	4110
Lime & Shale	4110	4212
Lime - RTD	4212	4220

ROTARY DRILLING LOG

1-1-34W

COMPANY: PICKRELL DRILLING COMPANY
Litwin Bldg. Suite 205-110 N. Market
Wichita, Kansas 67202
LOCATION: Fikan AB #2
C NE SW Sec. 1-15-34
Rawlins Co., Kansas

Rotary Drilling Commenced 7-26-75

Rotary Drilling Completed 8-19-75

CONTRACTOR: PICKRELL DRILLING COMPANY
Wichita, Kansas

CASING RECORD: 8 5/8 surface casing set at 208 with 150 sacks cement.
5 1/2" casing set at 4216' with 125 sacks cement.

LOG

(Figures indicate bottom of formation — measurements from top of rotary bushing.)

Top Soil	208
Shale	290
Shale	1365
Shale	2190
Shale	2320
Sand	2410
Hard Sand	2445
Shale	2540
Sandy Lime	2570
Shale & Lime	2856
Shale	2886
Shale	3100
Shale	3130
Lime & Shale	3315
Lime & Shale	3473
Lime & Shale	3590
Shale & Lime	3710
Lime	3775
Lime	3857
Lime & Shale	3918
Sand	3935
Lime	3940
Lime	3965
Lime	3990
Lime	4025
Lime	4040
Lime & Shale	4065
Lime	4110
Lime & Shale	4212
Lime - RTD	4220

