


BRITISH-AMERICAN OIL CO.
G.F. Smith No. 1.

SEC. 12 T. 20 R. 16W.
CSL NW SE
660' E WL 330' N SL NW $\frac{1}{4}$ SE $\frac{1}{4}$

Total Depth. 3821 (3816 GL)
Comm. 8-25-41 Comp. 9-14-41
Shot or Treated.
Contractor.
Issued. 11-1-41

County Pawnee



CASING.

95/8" 735' cem.
5 1/2" 3816' cem.

Elevation.

Production. Pot. 410 B.

Figures Indicate Bottom of Formations.

| | |
|--------------------|------|
| shale and shells | 460 |
| sand | 610 |
| shale and shells | 741 |
| red bed and shells | 1085 |
| anhydrite | 1110 |
| shale and shells | 1435 |
| shale and salt | 1500 |
| shale and shells | 1910 |
| lime and sdy lime | 2208 |
| lime and shale | 2238 |
| lime | 2420 |
| lime and shale | 2493 |
| lime | 2570 |
| shale | 2620 |
| broken lime | 2644 |
| lime and shale | 2710 |
| broken lime | 2787 |
| shale and shells | 2925 |
| lime | 2972 |
| lime and shale | 3185 |
| lime | 3435 |
| shale and lime | 3490 |
| lime | 3706 |
| shale | 3730 |
| lime | 3821 |
| Total Depth. | |

3816 - 5' correction to ground level

Show gas and slight show oil 3796-3813.
Good show oil 3813-18

Top Arbuckle 3739 Corr. to Ground level.