

## DRILL STEM TEST REPORT

Prepared For: **American Warrior**

PO Box 300  
Garden City KS 67846

ATTN: Scott Corsair

**23 20 22 Ness KS**

**Cox 2-23**

Start Date: 2007.08.10 @ 06:46:11

End Date: 2007.08.10 @ 13:36:50

Job Ticket #: 28933      DST #: 1

Trilobite Testing, Inc

PO Box 362 Hays, KS 67601

ph: 785-625-4778 fax: 785-625-5620



**TRILOBITE**  
**TESTING, INC.**

## DRILL STEM TEST REPORT

American Warrior  
PO Box 300  
Garden City KS 67846  
ATTN: Scott Corsair

**Cox 2-23**

**23 20 22 Ness KS**

Job Ticket: 28933

DST#: 1

Test Start: 2007.08.10 @ 06:46:11

### GENERAL INFORMATION:

Formation: **Mississippian**

Deviated: No Whipstock: ft (KB)

Time Tool Opened: 09:15:21

Time Test Ended: 13:36:50

Test Type: Conventional Bottom Hole

Tester: Brian Fairbank

Unit No: 41

Interval: **4292.00 ft (KB) To 4354.00 ft (KB) (TVD)**

Total Depth: 4354.00 ft (KB) (TVD)

Hole Diameter: 7.88 inches Hole Condition:

Reference Elevations: 2204.00 ft (KB)

2200.00 ft (CF)

KB to GR/CF: 4.00 ft

**Serial #: 8018**

**Inside**

Press@RunDepth: 46.96 psig @ 4299.01 ft (KB)

Start Date: 2007.08.10

End Date:

2007.08.10

Capacity: 7000.00 psig

Last Calib.: 2007.08.10

Start Time: 06:46:11

End Time:

13:36:50

Time On Btm: 2007.08.10 @ 09:12:36


Time Off Btm: 2007.08.10 @ 11:33:20

TEST COMMENT: IFP Weak blow throughout 1/2" - 2"

ISI No blow back

FFP Sur blow throughout

FSI No blow back



### PRESSURE SUMMARY

| Time (Min.) | Pressure (psig) | Temp (deg F) | Annotation           |
|-------------|-----------------|--------------|----------------------|
| 0           | 2079.94         | 112.19       | Initial Hydro-static |
| 3           | 23.62           | 111.37       | Open To Flow (1)     |
| 48          | 34.82           | 114.99       | Shut-In(1)           |
| 77          | 1301.63         | 115.44       | End Shut-In(1)       |
| 77          | 38.78           | 114.75       | Open To Flow (2)     |
| 109         | 46.96           | 116.05       | Shut-In(2)           |
| 137         | 1284.33         | 116.97       | End Shut-In(2)       |
| 141         | 2039.04         | 117.53       | Final Hydro-static   |

### Recovery

| Length (ft) | Description        | Volume (bbl) |
|-------------|--------------------|--------------|
| 45.00       | WM 5%W 95%M        | 0.63         |
| 15.00       | WOCM 17%O 3%W 80%M | 0.21         |
| 5.00        | FREE OIL 98%O 3%M  | 0.07         |
|             |                    |              |
|             |                    |              |
|             |                    |              |

### Gas Rates

|  | Choke (inches) | Pressure (psig) | Gas Rate (Mcf/d) |
|--|----------------|-----------------|------------------|
|--|----------------|-----------------|------------------|



**TRILOBITE**  
TESTING, INC.

## DRILL STEM TEST REPORT

TOOL DIAGRAM

American Warrior

Cox 2-23

PO Box 300  
Garden City KS 67846

23 20 22 Ness KS

Job Ticket: 28933

DST#: 1

ATTN: Scott Corsair

Test Start: 2007.08.10 @ 06:46:11


### Tool Information

|                           |                    |                       |                         |                        |             |
|---------------------------|--------------------|-----------------------|-------------------------|------------------------|-------------|
| Drill Pipe:               | Length: 4292.00 ft | Diameter: 3.80 inches | Volume: 60.21 bbl       | Tool Weight:           | 2500.00 lb  |
| Heavy Wt. Pipe:           | Length: 0.00 ft    | Diameter: 0.00 inches | Volume: 0.00 bbl        | Weight set on Packer:  | 25000.00 lb |
| Drill Collar:             | Length: 0.00 ft    | Diameter: 0.00 inches | Volume: 0.00 bbl        | Weight to Pull Loose:  | 55000.00 lb |
|                           |                    |                       | Total Volume: 60.21 bbl | Tool Chased            | 0.00 ft     |
| Drill Pipe Above KB:      | 27.00 ft           |                       |                         | String Weight: Initial | 48000.00 lb |
| Depth to Top Packer:      | 4292.00 ft         |                       |                         | Final                  | 48000.00 lb |
| Depth to Bottom Packer:   | ft                 |                       |                         |                        |             |
| Interval between Packers: | 62.02 ft           |                       |                         |                        |             |
| Tool Length:              | 89.02 ft           |                       |                         |                        |             |
| Number of Packers:        | 2                  | Diameter: 6.75 inches |                         |                        |             |

Tool Comments:

| Tool Description | Length (ft) | Serial No. | Position | Depth (ft) | Accum. Lengths                |
|------------------|-------------|------------|----------|------------|-------------------------------|
| Shut In Tool     | 5.00        |            |          | 4270.00    |                               |
| Hydraulic tool   | 5.00        |            |          | 4275.00    |                               |
| Jars             | 5.00        |            |          | 4280.00    |                               |
| Safety Joint     | 2.00        |            |          | 4282.00    |                               |
| Packer           | 5.00        |            |          | 4287.00    | 27.00 Bottom Of Top Packer    |
| Packer           | 5.00        |            |          | 4292.00    |                               |
| Stubb            | 1.00        |            |          | 4293.00    |                               |
| Perforations     | 5.00        |            |          | 4298.00    |                               |
| Change Over Sub  | 1.00        |            |          | 4299.00    |                               |
| Recorder         | 0.01        | 8018       | Inside   | 4299.01    |                               |
| Blank Spacing    | 31.00       |            |          | 4330.01    |                               |
| Change Over Sub  | 1.00        |            |          | 4331.01    |                               |
| Perforations     | 20.00       |            |          | 4351.01    |                               |
| Recorder         | 0.01        | 13548      | Outside  | 4351.02    |                               |
| Bullnose         | 3.00        |            |          | 4354.02    | 62.02 Bottom Packers & Anchor |

**Total Tool Length: 89.02**



**TRILOBITE**  
**TESTING, INC.**

## DRILL STEM TEST REPORT

### FLUID SUMMARY

American Warrior

Cox 2-23

PO Box 300  
Garden City KS 67846

23 20 22 Ness KS

Job Ticket: 28933

DST#: 1

ATTN: Scott Corsair

Test Start: 2007.08.10 @ 06:46:11

### Mud and Cushion Information

Mud Type: Gel Chem

Cushion Type:

Oil API:

deg API

Mud Weight: 9.00 lb/gal

Cushion Length:

ft

Water Salinity:

7000 ppm

Viscosity: 46.00 sec/qt

Cushion Volume:

bbl

Water Loss: 11.96 in<sup>3</sup>

Gas Cushion Type:

Resistivity: ohm.m

Gas Cushion Pressure:

psig

Salinity: 4200.00 ppm

Filter Cake: inches

### Recovery Information

Recovery Table

| Length<br>ft | Description        | Volume<br>bbl |
|--------------|--------------------|---------------|
| 45.00        | WM 5%W 95%M        | 0.631         |
| 15.00        | WOCM 17%O 3%W 80%M | 0.210         |
| 5.00         | FREE OIL 98%O 3%M  | 0.070         |

Total Length: 65.00 ft

Total Volume: 0.911 bbl

Num Fluid Samples: 0


Num Gas Bombs: 0


Serial #:

Laboratory Name:

Laboratory Location:

Recovery Comments:





# TRILOBITE TESTING INC.

P.O. Box 362 • Hays, Kansas 67601

28933

10495

## Test Ticket

|                                                                                |                                |                            |
|--------------------------------------------------------------------------------|--------------------------------|----------------------------|
| Well Name & No. <u>Cox 2-23</u>                                                | Test No. <u>1</u>              | Date <u>8-10-07</u>        |
| Company <u>American Warrior</u>                                                | Zone Tested <u>Mississippi</u> |                            |
| Address <u>PO Box 399 Garden City, KS 67846</u>                                | Elevation <u>2204</u>          | KB <u>2200</u> GL          |
| Co. Rep / Geo. <u>Scott Corcoran</u>                                           | Rig <u>Petromark 1</u>         |                            |
| Location: Sec. <u>23</u> Twp. <u>20<sup>s</sup></u> Rge. <u>22<sup>w</sup></u> | Co. <u>Ness</u>                | State <u>K</u>             |
| Comment: _____                                                                 |                                | Release date / time: _____ |

|                                                               |                                    |                                     |
|---------------------------------------------------------------|------------------------------------|-------------------------------------|
| Interval Tested <u>4292-4354</u>                              | Initial Str Wt./Lbs. <u>48,000</u> | Unseated Str Wt/Lbs. <u>48,000</u>  |
| Anchor Length <u>62</u>                                       | Wt. Set Lbs. <u>25,000</u>         | Wt. Pulled Loose/Lbs. <u>55,000</u> |
| Top Packer Depth <u>4287</u>                                  | Tool Weight <u>2500</u>            |                                     |
| Bottom Packer Depth <u>4292</u>                               | Hole Size 7 7/8" <u>-</u>          | Rubber Size 6 3/4" <u>-</u>         |
| Total Depth <u>4354</u>                                       | Wt. Pipe Run <u>-</u>              | Drill Collar Run <u>-</u>           |
| Mud Wt. <u>9.0</u> LCM <u>-</u> Vis. <u>46</u> WL <u>12.0</u> | Drill Pipe Size <u>4 1/2 X 41</u>  | Ft. Run <u>4292</u>                 |
| Blow Description <u>IFP- weak blow throughout 1/2-2</u>       |                                    |                                     |
| <u>ISI- no blow back</u>                                      |                                    |                                     |
| <u>FFP- sur blow throughout</u>                               |                                    |                                     |
| <u>FSI- no blow back</u>                                      |                                    |                                     |

|                                 |                              |                     |                                        |
|---------------------------------|------------------------------|---------------------|----------------------------------------|
| Recovery - Total Feet <u>65</u> | GIP <u>-</u>                 | Ft. in DC <u>-</u>  | Ft. in DP <u>65</u>                    |
| Rec. <u>5</u>                   | Feet of <u>Free oil</u>      | %gas <u>98</u> %oil | %water <u>2</u> %mud                   |
| Rec. <u>15</u>                  | Feet of <u>WOCM</u>          | %gas <u>17</u> %oil | <u>3</u> %water <u>80</u> %mud         |
| Rec. <u>45</u>                  | Feet of <u>WM</u>            | %gas <u>-</u> %oil  | <u>5</u> %water <u>95</u> %mud         |
| Rec. <u>-</u>                   | Feet of <u>-</u>             | %gas <u>-</u> %oil  | %water <u>-</u> %mud                   |
| Rec. <u>-</u>                   | Feet of <u>-</u>             | %gas <u>-</u> %oil  | %water <u>-</u> %mud                   |
| BHT <u>117</u>                  | *F Gravity <u>-</u>          | *API D @ <u>-</u>   | *F Corrected Gravity <u>7.574</u> *API |
| RW <u>.567</u> @ <u>100</u>     | *F Chlorides <u>7000</u> ppm | Recovery <u>-</u>   | Chlorides <u>4200</u> ppm System       |

|                                                |                                      |                                      |
|------------------------------------------------|--------------------------------------|--------------------------------------|
| (A) Initial Hydrostatic Mud <u>2080</u> PSI    | Recorder No. <u>8018</u>             | Test <u>✓</u> <u>1200</u>            |
| (B) First Initial Flow Pressure <u>24</u> PSI  | (depth) <u>4299</u>                  | Jars <u>✓</u> <u>250</u>             |
| (C) First Final Flow Pressure <u>35</u> PSI    | Recorder No. <u>13548</u>            | Safety Jt. <u>✓</u> <u>75</u>        |
| (D) Initial Shut-In Pressure <u>1302</u> PSI   | (depth) <u>4351</u>                  | Circ Sub <u>-</u>                    |
| (E) Second Initial Flow Pressure <u>39</u> PSI | Recorder No. <u>-</u>                | Sampler <u>-</u>                     |
| (F) Second Final Flow Pressure <u>47</u> PSI   | (depth) <u>-</u>                     | Straddle <u>-</u>                    |
| (G) Final Shut-In Pressure <u>1284</u> PSI     | Initial Opening <u>45</u>            | Ext. Packer <u>-</u>                 |
| (Q) Final Hydrostatic Mud <u>2039</u> PSI      | Initial Shut-In <u>30</u>            | Shale Packer <u>-</u>                |
|                                                | Final Flow <u><del>45</del> 30</u>   | Ruined Packer <u>-</u> <u>181.25</u> |
|                                                | Final Shut-In <u>30</u>              | Mileage <u>✓</u> <u>145 RT</u>       |
|                                                | T-On Location <u>0542</u>            | Sub Total: <u>1706.75</u>            |
|                                                | T-Started <u>0646</u>                | Std. By <u>-</u>                     |
|                                                | T-Open <u>0915</u>                   | Acc. Chg: <u>-</u>                   |
|                                                | T-Pulled <u><del>1130</del> 1130</u> | Other: <u>-</u>                      |
|                                                | T-Out <u>1337</u>                    | Total: <u>-</u>                      |

Approved By \_\_\_\_\_

Our Representative Brian Fairbank (thb)

7.75

TRILOBITE TESTING INC. SHALL NOT BE LIABLE FOR DAMAGED OF ANY KIND OF THE PROPERTY OR PERSONNEL OF THE ONE FOR WHOM A TEST IS MADE, OR FOR ANY LOSS SUFFERED OR SUSTAINED, DIRECTLY OR INDIRECTLY, THROUGH THE USE OF ITS EQUIPMENT, OR ITS STATEMENTS OR OPINION CONCERNING THE RESULTS OF ANY TEST. TOOLS LOST OR DAMAGED IN THE HOLE SHALL BE PAID FOR AT COST BY THE PARTY FOR WHOM THE TEST IS MADE.

# CHART PAGE

This is a photocopy of the actual AK-1 recorder chart

