WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas 14-20-24W


Company- KEWANEE OIL COMPANY
Farm- Petersilie No. 2

SEC. 14 T. 20 R. 24W
SE NE SW
(990' fr. NL & 330' fr. EL of SW/4)

Total Depth. 4485' C.M. - PB 4451' C.M.
Comm. 7-30-58 Comp. 8-12-58
Shot or Treated.
Contractor. Graham-Michaelis Drlg. Co.
Issued. 10-25-58

County Ness

KANSAS



Elevation. 2328' C.M.

CASING:
8 5/8" 522.98' C.M. cem. w/350 sx.
5 1/2" 4479.70' C.M. cem. w/100 sx.

Production. Swabbed 400.22 Bbls. oil in 14 hours.

Figures Indicate Bottom of Formations.

surface	0
shale & shells	425
shale, red bed & anhydrite	526
shale & shells	1245
lime, shale & anhydrite	1930
lime & shale	2280
lime & shale w/strks chalk	3430
lime & shale	3540
lime	3861
lime & chalk	4020
lime	4061
Conglomerate	4364
lime & conglomerate	4392
lime	4430
lime	4485
Total Depth.	

Plugged back TD 4451' C.M.

SAMPLE TOPS - C. M. MEASUREMENT

Marmaton	4139
Heebner	3720
Toronto	3739
Lansing-Kansas City	3791
Base Kansas City	4119
Cherokee	4281
Penn. Conglomerate	4363
Mississippi	4393
Total Depth	4485

SCHLUMBERGER LOG TOPS - C.M. Measurement

Heebner	3713
Toronto	3734
Lansing-Kansas City	3789
Base Kansas City	4124
Marmaton	4140
Cherokee	4279
Conglomerate	4354
Mississippi	4391
Total Depth	4482

Treating Record: Acidized perfs. 4412-4417 w/259 gals. mud acid. Acidized perfs. 4394-4402 w/500 gals. mud acid.

Perforating Record: Perf. 4412' to 4417' & 4394' to 4402' with 6 bullets per foot.

2 3/8" O.D. Tubing (144 joints) set at 4447.93' C.M. with top of perf. at 4412.80' C.M.