

Carlock Et Al  
Conrad No. 1.

SEC. 15 T.20 R.6W  
CWL SW NE

Total Depth. 3390'  
Comm. 5-4-40 Comp. 6-2-40  
Shot or Treated.  
Contractor. E.J. Shaffer.  
Issued. 6-29-40

County. Rice



CASING:  
10 $\frac{3}{4}$ " 116'  
7" 3309 $\frac{1}{2}$ '

Elevation. 1606

Production. Dry

Figures Indicate Bottom of Formations.

|                          |                    |
|--------------------------|--------------------|
| surface clay             | 40                 |
| clay & shells            | 65                 |
| red rock & shells        | 350                |
| anhydrite, shale, shells | 550                |
| shale & salt             | 865                |
| shale & lime             | 930                |
| anhydrite                | 954                |
| shale & shells           | 1240               |
| shale sdy                | 1290               |
| lime sdy                 | 1395               |
| shale & lime             | 1660               |
| lime sdy & shale         | 2005               |
| shale & lime             | 2180               |
| shale                    | 2195               |
| shale & lime sdy         | 2292               |
| lime                     | 2600               |
| lime sdy                 | 2695               |
| shale & lime             | 2710               |
| shale                    | 2800               |
| lime K.C. (porous)       | 2808               |
| lime                     | 2900               |
| lime porous              | 2940               |
| lime                     | 2960               |
| shale & lime             | 3025               |
| lime                     | 3075               |
| shale & lime             | 3309 $\frac{1}{2}$ |
| ohat                     | 3388               |
| shale blk HFW            | 3390               |
| Total Depth.             |                    |

Run 3309 $\frac{1}{2}$ ' of 7" csg, over  
all measurement 3328'