

TULSA OIL CORP.  
J. Mattson No. 1.

SEC. 25 T. 20 R. 6W  
CNL NE SE

Total Depth. 3372'  
Comm. 3-6-40 Comp. 3-19-40  
Shot or Treated.  
Contractor. Pem Drlg. Co., Inc.  
Issued. 5-25-40

County. Rice



CASING:  
10" 167'  
5 3/16" 3315'

Elevation. 1525

Production. Pot. 88 B.

Figures Indicate Bottom of Formations.

surface shale	40	shale & chert	3364
sand	60	chert	3368
shale & red rock	161	shale break	3371
red rock	190	lime	3372
shale & shells	460	Total Depth.	
shale & salt	680		
shells & salt	720		
shale & shells	810	Top Topeka lime	2620
lime	905		
shale & brkn lime	1060		
brkn lime	1110		
lime sdy	1135		
brkn lime	1150		
lime	1210		
brkn lime	1310		
shale	1350		
shale & brkn lime	1470		
shale & lime shells	1520		
lime	1555		
lime brkn	1603		
shale	1650		
shale & lime	1765		
shale & lime shells	1815		
lime	1833		
shale & shells	1890		
lime brkn	1980		
shale & lime	1990		
shale & lime shells	2073		
shale & lime brkn	2115		
lime brkn	2125		
shale	2180		
shale & lime	2210		
shale	2215		
lime	2320		
lime brkn	2330		
lime	2410		
shale	2422		
lime	2515		
shale & lime	2620		
lime Topeka	2651		
lime	2812		
shale & brkn lime	2886		
lime	3030		
shale & lime	3125		
lime	3138		
shale hrd	3145		
shale	3155		
lime	3170		
shale & lime	3235		
shale & lime shells	3258		
lime brkn	3270		
conglomerate	3280		
chat	3285		
no log	3300		
chat	3325		
chat sft	3330		
chat hrd	3335		
chert	3343		
shale	3347		
chat	3349		